

connecting the future



HTS 4DC - 4 way splitter

Article number: 347014

Product description:

HTS 4DC - 4 way splitter. Low insertion loss. All ports impedance 75 Ohm. High isolation. Class A shielding - ideal for your TV system.

Specifications

ORDER INFORMATION	
EAN Number	5702663470149
SHIELDING	
Shielding efficiency VHF/UHF	> 110.0 dB
FREQUENCY	
Frequency range	5...1000 MHz
LOSS	
Insertion loss (in-out) 5-40 Mhz	< 6.8 dB
Insertion loss (in-out) 40-470 MHz	< 7.0 dB

Insertion loss (in-out) 470-860 MHz	< 7.5 dB
Insertion loss (in-out) 860-1000 MHz	< 8.0 dB
ISOLATION	
Isolation (tap-tap) 5-40 MHz	> 26.0 dB
Isolation (tap-tap) 40-470 MHz	> 28.0 dB
Isolation (tap-tap) 470-860 MHz	> 24.0 dB
Isolation (tap-tap) 860-1000 MHz	> 24.0 dB
RETURN LOSS	
Return loss (in-out) 5-40 MHz	> 20.0 / > 22.0 dB
Return loss (in-out) 40-470 MHz	> 20.0 / > 22.0 dB
Return loss (in-out) 470-860 MHz	> 20.0 / > 20.0 dB
Return loss (in-out) 860-1000 MHz	> 20.0 / > 20.0 dB
ELECTRICAL	
Impedance	75 Ω
OPERATIONAL	
DC Passthrough	Yes
CONNECTORS	
Number of outputs	4
Connector Type	F-female
MECHANICAL	
Product Depth	16 mm
Product Height	50 mm
Product Width	74 mm
Packing QTY	1
Packaging Height	0,020 m
Packaging Width	0,050 m
Packaging Depth	0,070 m
Net Weight	0,045 kg
Tara Weight	0,006 kg
Total Weight	0,051 kg

