



WI-POE11S-48V
48V 100Mbps
PoE Splitter Datasheet



Highlights

- 2*100Mbps RJ45 Ports with 1 PoE Input and 1PoE Output
- IEEE 802.3af/at compliant
- Delivers power up to 100 meters
- 12V 1A DC Output
- Plug-and-Play, requires no configuration



Typical Applications



Description

what this product does

The PoE Splitter WI-POE11S-48V fully complies with IEEE 802.3af/at standard, and can work with all IEEE 802.3af/at PoE compliant PSE (Power Supply Equipment) or PoE Switch or PoE Injector such as WI-TEK's WI-POE31-48V, WI-POE51-48V or WI-POE55-60W, or other equivalent product, to deliver 12V 1A Direct Current to where there are no power line or outlet, where you wish to fix device such as AP, IP Camera or IP Phone, etc.

Specifications

HARDWARE FEATURES

Interface	2 10/100Mbps RJ45 Ports
Network Media	10BASE-T: UTP category 3, 4, 5 cable (Max 100m) EIA/TIA-568 100Ω STP (Max 100m) 100BASE-TX: UTP category 5, 5e cable (Max 100m) EIA/TIA-568 100Ω STP (Max 100m)
Fan Quantity	Fanless
PoE IN PIN	4,5+ 7,8- and 1,2+ 3,6-
PoE Output PIN	1,2+ 3,6-
DC Output	12V 1A

HARDWARE FEATURES

Dimensions (W x D x H)	80*22*20mm
Backbound Bandwidth	200Mbps

SOFTWARE FEATURES

Transmission Method	Store-And-Forward
Advanced Functions	Priority Function Mac Address Auto-Learning And Auto-Aging Store and forward IEEE 802.3x flow control for Full-duplex Mode Backpressure for Half-duplex Mode

OTHERS

Certification	CE, FCC, RoHS
Package Contents	POE Switch Electric Line Guide Book/Warranty Card
Environment	Operating Temperature: -10°C~55°C