

126501 GRAVITY

An incredibly comfortable full body fall arrest harness.

TOWERS/INDUSTRY

ROOFS

CONSTRUCTION

The padded structure wraps the body for the most uniform distribution of pressure.
 Patented STS automatic buckles on the waist and legs make it extremely easy to put on and take off.
 Two fall arrest attachment points: double textile loop in the front, aluminium alloy ring in the back.
 Textile loops on the sides for work positioning.

2 sizes.



Ref.	Product name Nombre del producto	Size Tallas	Weight Peso		Chest Pecho	Waist Cintura	Legs Perneras	Height Altura	CE		EAC	Attachment points Puntos de anclaje
			g	oz	A (cm)	B (cm)	C (cm)	D (cm)	EN 358	EN 361		
126501	GRAVITY	S-L	1810	63.9	80-120	70-110	45-65	55-75	•	•	•	
		L-XXL	1930	68.1	90-140	80-130	55-75	65-85	•	•	•	

126501 **GRAVITY**



GRAVITY

- ① Padded structure wraps the body for the most uniform distribution of pressure.
- ② Patented STS automatic buckles on the waist and legs make it extremely easy to put on and take off.
- ③ Double textile loop integrated with the structure for the frontal fall arrest attachment point.
- ④ New forged aluminium alloy ring for the back fall arrest attachment point.
- ⑤ Textile loops on the sides for work positioning.
- ⑥ New lightweight buckles made from carbon steel C50.
- ⑦ Belt padded with 3D mesh for better comfort and breathable.
- ⑧ Comfortable padded leg-loops.
- ⑨ Adjustable back webbing for best comfort.
- ⑩ Main webbings made from polyester, 44 mm wide.
- ⑪ Reflective parts.
- ⑫ Sternal strap with plastic buckle.
- ⑬ Gear-loops with protective plastic tube.
- ⑭ CE label with serial number and batch number.



②