

Centre d'Essais de Fontaine 17, Bd Paul Langevin 38600 FONTAINE - France Tél. +33.(0)4.76.53.52.22

# CONFORMITY CERTIFICATE N° 20.1699 3/A

# 1. Applicant

Applicant: Mr. Jean-Charles IANZ

Manufacturer: TRACTEL SAS - RD619 - BP38 Saint-Hilaire-Sous-Romilly - 10102 ROMILLY-SUR-

SEINE- France

## 2. Equipment

Type of equipment: Type A Anchor device – EN 795:2012 and Technical Specification CEN/TS 16415:2013

Trademark: TRACTEL

Model: DAVITRAC + Embase murale déportée

Reference: 286819 + 210118

#### 3. Description

Type A anchor device, made of:

- a bracket, DAVITRAC, reference 286819, in 6082 T6 aluminum alloy, dimensions 1921,5mm x 907,3mm, including 3 anchor points, with 2 placed on the articulation part of the bracket and 1 on the head of the bracket.
- a fixing base, model Embase murale déportée, in S235 and S355 steel, made of a connector board, dimensions 230mm x 230mm and a sheath, intern diameter 120mm, including two assembly plates. Base with wall fixing. Equipment also assessed according to the requirement of Technical Specification CEN/TS 16415:2013, for use by 2 people without exceed 1 people by anchor point (detailed in the conformity report n°20.1699).

#### 4. Technical referential

The assessment of conformity was conducted taking into account the provisions of:

- European standard EN 795:2012 "Personal fall protection equipment Anchor devices ".
- Technical Specification CEN/TS 16415:2013 "Personal fall protection equipment Anchor devices Recommendations for anchor devices for use by more than one person simultaneously" CEN/TS 16415:2013.

## 5. Conditions for use

This anchor device - type A - is not considered as Personal Protective Equipment but it is intended be used as part, together with other components, of a personal fall protection system in accordance with standard EN363. It is intended to be removable from the structure and to be part of the anchor.

#### 6. Conclusion

The type A anchor device, trade mark "TRACTEL", model "DAVITRAC + Embase murale déportée" complies with the provisions of European standard EN 795:2012 and of the technical specification TS 16415 of January 2013 for use by 2 people.

05/02/2021
The technical assessment manager

CINDY BOUN
Validation électronique

validation electroniqu

This certificate includes one page. No duplicate will be issued.