## 2132050 - 2132100 - 2132150 - 2132200 ANCHOR CABLE



TREE CLIMBING TOWERS/INDUSTRY CONSTRUCTION

AND DE CONTRACTOR

to the cable strands. Perfect for creating cut-resistant and anti-abrasion anchors. Can also be teamed with EN 355 certified energy absorbers to create anti-cut fall arrest lanyards. 2017 UPDATE: meets ANSI Z359.1 standard for Anchorage Devices.


> Plastic protective tube Outer diameter: 15mm

7 mm zinc-plated steel cables with eyelets at the ends

protected with a 15 mm plastic tube to prevent damage

Wire cable Diameter:d.7mm, Construction type: AZN 7x19 CE marking Galvanized steel including individual serial number Protective metal thimbles

> Pure aluminium splicing Breaking load: 32kN



Ref.	Product name Nombre del producto	Weight Peso		Strength Resistencia	CE		ANSI	ERC
		g	oz	kN	EN 354	EN 795/B	Z359.1	
2132050	ANCHOR CABLE 50 cm	240	8.5	32	•	•	•	•
2132100	ANCHOR CABLE 100 cm	410	14.5	32	•	•	•	•
2132150	ANCHOR CABLE 150 cm	580	20.5	32	•	•	•	•
2132200	ANCHOR CABLE 200 cm	750	26.5	32	•	•	•	•