

Application

The life line tirsaf™ kit is selling with a tirfor™ T3 , a tirsafe™, a wire rope 20m or 30m meter with a connector MR9 and 2 slings of 2 meters.

The tirsafe™ is a shock absorbing anchorage device, designed for attaching 8 mm wire rope lifelines.

It performs three functions:

Pretensioning indicator/shock absorber/fall indicator.

It is simple and quick to fit, and can be used with a tirfor™ T3 tensioner fitted with a galvanised wire rope, minimum diameter 8 mm and maximum length 30 m.

Once it has been fitted, the temporary lifeline equipped with the tirsafe™ can take 3 peoples of 150kg simultaneously



Features :

Code No.	Description	Min. qty	Size L x W x H mm	Weight kg With packaging	Description
280559	Tirsafe™ 150kg 20m	1	600x400x200	17.00kg	Cardboard box
276149	Tirsafe™ 150kg 30m	1	600x400x200	19.31kg	Cardboard box
Optional accessories					
006139	tirfor™ T3 tensioner	1	470X100X350	7.88kg	Cardboard box
066688	INRS™ absorber	1	190X30X122	1.07kg	PU BAG
066858	Tension indicator	1	183.5Xø50	0.78kg	PU BAG
039822	Quick carabiner	1	90.5X10X46.36	0.14kg	PU BAG
279089	Galvanised steel sling 2m	1	200X10X30	0.75kg	PU bag
076092	Galvanised 8 mm wire rope 20m	1	ø350x80	7.00kg	No packaging
082062	Galvanised 8 mm wire rope 30m	1	ø350x80	9.30kg	No packaging

Norm :

- * Conforms with standard EN 795/ 2012 – EAC TC 09/2011
- * Conforms with standard EAC TC 09/2011
- * Conforms with CEN/TS 16415:2017 (3x150 kg)

Code:

Name	New code	Stat code	EAN code
Tirsafe™ 150kg 20m	280559	41210	3600232805595
Tirsafe™ 150kg 30m	276149	41210	3600232761495
accessories			
tirfor™ T3 tensioner	006139	33085	3600230061399
INRS™ absorber	066688	41116	3600230666884
Tension indicator	066858	41116	3600230668581
Quick carabiner MR9	039822	42410	3600230398228
Galvanised steel sling 2m	279089	11290	3600232790891
Galvanised 8 mm wire rope 20m+MR9	076092	41210	3600230760926
Galvanised 8 mm wire rope 30m+MR9	082062	41210	3600230820620