SANIA

Entry for the race seriously Feeling a new driving which collaboration with peripheral devices produces and more than anything, more enjoyable world attraction of MT-4S to add evolution & scalability to MT-4 of deep R/C

MT-4S
Special Combo Set



• Frequency: 2.4GHz - FHSS4/FHSS3

• Input Voltage: 4.8 - 7.4 V

• Weight: 6.6g

• Dimensions: 30.0x23.3x14.0mm

Spread spectrum system

 Sanwa Synchronized Link (SSL) function support

Super Response (SSR) support

Lightest receiver in class

WORLD CHAMPION 2014 - 2015

Transmitter MT-4S

incl. Receiver - Servo

MT-4S&ERS-962 - 488928

- 2.4GHz
- LCD backlight
- CODE AUX

(with CODE AUX name function)

- Super fast F.H.S.S.-4 technology
- Antenna integrated into the handle
- High-quality case and workmanship
- Menu selection comfortable operation with scroll wheel
- Telemetry (displays motor temperature, RPM and receiver V during operation)
- Telemetry Logging
- Data logger: up to 120 measuring points during the run (grading selectable)
- Direct Model Select
- Dual Rate, Expo, Trim/Sub Trim, Servo Reverse and Endpoint Adjustment
- Adjustable servo operation speed
- Anti-Lock Braking System
- Programmable model names and 18 model memory
- Model Select Shortcut (Direct Model)
- Compatible with older receivers due to changeable modulation (FH2/FH3/FH4T)
- Adjustable spring tension for steering and throttle
- Adjustable Throttle Trigger
- Changeable throttle mode (5:5 or 3:7)
- Programmable Low Voltage Alarm
- Additional grip pad for bigger hands
- Timer
- AUX1 / AUX2



Servo ERS-962

Speed: 0.11sec/60°(7.4V)

• Torque: 25.3kg ·cm(7.4V) 15.2kg · cm(6V)

• Dimensions: 40.3x20.2x35.9mm

• Weight: 62g

• LiPo (2cell) Battery support

Waterproof (IPX4)

- Coreless motor
- Double bearing
- Full Metal gear (Incl. Steel Gear)
- Aluminum heatsink

04/2016



Jegindøvej 21, DK - 8800 Viborg +45 8928 1800 - salg@veste.dk
Only whole sale, no sale to END users – Please contact your nearest Dealer

