

SYNTH C4 5W30

SYNTHETIC MOTOR OIL

This is a full synthetic lubricant based on carefully selected very high quality base oils, specifically formulated to provide superior protection of the after-treatment systems of Renault engines.



★ APPLICATIONS

Gasoline and diesel engines of passenger cars with or without turbo which are equipped with a DPF and a TWC (Three-Way Catalyst).

★ PERFORMANCE LEVEL

- ACEA: C4-12
- MB: 226.51
- MB: 229.51
- RENAULT: RN 0720

★ FEATURES

Aftertreatment protection : full aftertreatment system protection.
Total engine protection : outstanding engine cleanliness and durability.
Fuel economy : lower fuel consumption and CO2 emissions.

★ CHARACTERISTICS

	unit	average value
Density at 15 °C	kg/l	0.851
Viscosity -30 °C	mPas	6020
Viscosity 40 °C	mm ² /s	66.00
Viscosity 100 °C	mm ² /s	12.10
Viscosity Index		174
Flash Point COC	°C	228
Pour Point	°C	-39
Total Base Number	mgKOH/g	7.3
Sulphate Ash	%	0.49

★ PACKAGING



12x1L



4x4L



3x5L



20L



60L



210L



IBC

Vroman NV - Oudenaardestraat 49 | 8570 Vichte | Belgium

T +32 56 72 62 29 - F +32 56 72 67 37

E info@ardeca-lubricants.be