
CABLE GLAND M-TYPE



SPECIFICATION

Material: Polyamid

Rubber gasket: Nitrile rubber(NBR)

Protection Grade: IP68

Ambient temperature: stick~40°C to 100°C, for short time 120°C,

Dynamic -20°C to 80°C, For short time 100°C

Color: Gray RAL7035, Black RAL9005

CE Approved

UL/CS File: E240925

Model	Kabel Ø	GL	H	Nyckelvidd	AG	Art.Nr	Art.Nr
Yttergånga	mm	mm	mm	mm	mm	GRAY 7035	BLACK 9005
M12x1,5	3-6,5	8	22	16	12	10000-M1208060	10000-M1208061
M16x1,5	5-10	8	27	22	16	10000-M1608100	10000-M1608101
M20x1,5	6-12	9	28	24	20	10000-M2009120	10000-M2009121
M20x1,5	10-14	10	30	27	20	10000-M2010140	10000-M2010141
M25x1,5	13-18	10	35	33	25	10000-M2510180	10000-M2510181
M32x1,5	12-21	11	34	36	32	10000-M3211210	10000-M3211211
M40x1,5	20-26	14	48	52	40	10000-M4014260	10000-M4014261
M50x1,5	25-31	14	49	60	50	10000-M5014310	10000-M5014311
M63x1,5	37-44	14	50	67	63	10000-M6314440	10000-M6314441