
CABLE GLAND PG-TYPE



SPECIFICATION

Material: Polyamid

Rubber gasket: Nitrile rubber(NBR)

Protection Grade: IP68

Ambient temperature: stick~40°C to 100°C, for short time 120°C,

Dynamic -20°C to 80°C, For short time 100°C

Color: Gray RAL7035, Black RAL9005

CE Approved

UL/CS File: E240925

Model	Kabel Ø	GL	H	Nyckelvidd	AG	Art.Nr	Art.Nr
Yttergånga	mm	mm	mm	mm	mm	GRAY 7035	BLACK 9005
PG7/12	3-6,5	8	22	16	12	10000-MP0708060	10000-MP0708061
PG9/16	4-8	8	26	19	16	10000-MP0908080	10000-MP0908081
PG11/18	5-10	8	27	22	18	10000-MP1108100	10000-MP1108101
PG13,5/20	6-12	9	28	24	20	10000-MP1309120	10000-MP1309121
PG16/22	10-14	10	30	27	22	10000-MP1610140	10000-MP1610141
PG21/28	13-18	10	35	33	28	10000-MP2110180	10000-MP2110181
PG25/30	16-21	11	34	35/36	30	10000-MP2511210	10000-MP2511211
PG29/37	18-25	12	40	41/42	37	10000-MP2912250	10000-MP2912251
PG36/47	22-32	14	48	52/53	47	10000-MP3614320	10000-MP3614321
PG42/54	32-38	14	49	60/61	54	10000-MP4214380	10000-MP4214381
PG48/59	37-44	14	50	64/65	59	10000-MP4814440	10000-MP4814441