

# SKF Food Grade Lubricants

## General purpose food grade grease

### LGFP 2

SKF LGFP 2 is a clean, non-toxic bearing grease, which is based on medical white oil using an aluminium complex soap.

- High resistance to water
- Excellent grease life
- Excellent corrosion resistance
- An essentially neutral pH value
- NSF H1 registered and Halal and Kosher certified

#### Typical applications

- Multi-pack cassette bearings
- Wrapping machines
- Conveyor bearings
- Bottling machines



#### Available pack sizes

Packsizes	Designation	Packsizes	Designation
420 ml cartridge	LGFP 2/0.4	Electro-mechanical lubricators	
1 kg can	LGFP 2/1	TLSD series 125 ml	TLSD 125/FP2
18 kg pail	LGFP 2/18	TLSD series 125 ml refill	LGFP 2/SD125
180 kg drum	LGFP 2/180	TLSD series 250 ml	TLSD 250/FP2
Gas driven lubricators		TLSD series 250 ml refill	LGFP 2/SD250
LAGD series 125 ml	LAGD 125/FP2	Electro-mechanical lubricant dispensers	
		TLMR 101 series 380 ml refill (incl. battery)	LGFP 2/MR380B
		TLMR 201 series 380 ml refill	LGFP 2/MR380




## Technical data

Designation	LGFP 2/(pack size)		
NLGI consistency class	2	Corrosion protection	Emcor: – standard ISO 11007
DIN 51825 code	K2G-20		0–0 <sup>1)</sup>
Colour	Transparent	Water resistance	DIN 51 807/1, 3 hrs at 90 °C
Soap type	Aluminium complex		1 max.
Base oil type	Medical white oil	Oil separation	DIN 51 817, 7 days at 40 °C, static, %
Operating temperature range	–20 to +110 °C (–5 to +230 °F)		1–5
Dropping point DIN ISO 2176	>250 °C (>480 °F)	Rolling bearing grease life	ROF test
Base oil viscosity			L <sub>50</sub> life at 10 000 r/min., hrs
40 °C, mm <sup>2</sup> /s	150		1 000 at 110 °C (230 °F) <sup>1)</sup>
100 °C, mm <sup>2</sup> /s	15,3	EP performance	4–ball test,
Penetration DIN ISO 2137			welding load DIN 51350/4, N
60 strokes, 10 <sup>-1</sup> mm	265–295	Shelf life	1 100 min.
100 000 strokes, 10 <sup>-1</sup> mm	+30 max.	NSF Reg. No.	128004

<sup>1)</sup> Typical value

## Lubrication management

Just as asset management takes maintenance to a higher level, a lubrication management approach allows lubrication to be seen from a wider point of view. This approach helps to effectively increase machine reliability at a lower overall cost.



[skf.com](http://skf.com) | [mapro.skf.com](http://mapro.skf.com) | [skf.com/lubrication](http://skf.com/lubrication)

© SKF is a registered trademark of the SKF Group.

© SKF Group 2017

The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.

PUB MP/P8 12048/2 EN · June 2017

Certain image(s) used under license from Shutterstock.com.