

# BORRSTÅNGSFETT

## Omicron 98 "High performance tool joint grease"

### Description

Omicron 98 högprestandafett är ett korrosionsresistent borrhängfett med anti seize skydd och överlägsen vidhäftning på kraftigt belastade gängförband.

Omicron 98 är speciellt utvecklat för höga drifttemperaturer där korrosion, slag, och skärning uppträder i gängade maskinelement.

Omicron 98 gör delar montering och demontering lättare tack vare den höga halten fasta smörjmedel

Omicron 98 klarar lång livslängd och tål temperaturer upp till 1100 grader Celsius (utan kontakt med luft)

### Performance level

Conform API bulletin 5 A2

### Typiska egenskaper

ASTM Penetration	310
Zinc	50%
Drop point C	110
Sulfur 0,3%	0,3%
Temp wide	-25 - 140°C
Water washout at 66 C	3% max
Lead	0%
Evaporation (24hrs " 100 C)	0,5% max
Solids content	60 % min
Solids Nature	Copper, graphite & zinc (50% min)

## SMÖRJTEKNIK NORDEN AB

Utjordsvägen 14 802 91 GÄVLE SWEDEN Tel 077-1234567 Fax 026-107107 info@smorjteknik.se www.smorjteknik.se

The recommendations or suggestions made in this sheet are made without guarantee or representation as to results. The content of this sheet is correct to the best of our knowledge. We advise the reader to carefully evaluate the product choice for critical applications together with the supplier. We do not accept responsibility for damage as a consequence of incompleteness or, negligence and inaccuracies in this informationsheet. All terms of sale of the supplier can be applied here.