

# RAPTOR BAR

1532

**FITS: SOFTAIL: H-D RIGID OR DETACHABLE SIDE PLATES ON ALL '84-'85 SOFTTAILS (EXCEPT DEUCE) & '06-UP FLST MODELS (EXCEPT '06 FLSTFSE, '07-UP FLSTF, '08-UP FLSTSB) ALSO COMPATIBLE WITH KURYAKYN SIDE PLATES (P/N 8971 & 8972)**

**DYNA: H-D RIGID OR DETACHABLE SIDE PLATES ON ALL '06-UP DYNAS (EXCEPT '08-UP FXDF, '09-UP FXDFSE)**

**SPORTSTER: H-D DETACHABLE SIDE PLATES ON ALL '04-UP SPORTSTERS  
UNIVERSAL FITMENT FOR METRIC APPLICATIONS: KURYAKYN BACKREST MOUNTING STRAPS 1356, 1357, 1358 & UNIVERSAL FOR BACKREST MOUNTING STRAPS THAT ACCEPT A BACKREST WITH A 1/2" SQUARE BAR, 1/4-21 BOLT HOLES 1-1/4" APART & AN OUTSIDE WIDTH OF 8-3/4" WIDE**

PART #	INCLUDED
901532	1 Raptor Bar And Pad Assembly Including:
	1 Raptor Bar
	1 Raptor Bar Back Trim
	1 Raptor Bar Pad
	2 1/4"-20 x 1/2" SHCS 18-8
	1 Hardware Kit Including:
	4 1/4"-20 x 5/8" SHCS
	1 Front Trim (not used with back pad)
	1 Installation Instructions

Please read and understand entire instructions before starting installation.

## THANK YOU FOR CHOOSING KURYAKYN!

**IN ORDER TO PROTECT YOU AND OTHERS FROM POSSIBLE INJURY AND/OR PROPERTY DAMAGE OR LOSS, PLEASE PAY CLOSE ATTENTION TO ALL INSTRUCTIONS, WARNINGS, CAUTIONS AND ATTENTION NOTES REGARDING THE USE AND CARE OF THIS PRODUCT.**

**WARNING!** THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN POTENTIAL DEATH OR SERIOUS INJURY.

**CAUTION!** This indication alerts you to the fact that ignoring the contents described herein can result in potential injury or material damage.

**ATTENTION!** This indication alerts you to the fact that ignoring the contents described herein may negatively affect product performance and functionality.

### IMPORTANT NOTICE

Never operated the bike with a passenger with out having the pad on the Raptor Bar installed.

### PROCEDURE

**STEP 1** If you have saddle bags you will need to remove them so you can get to the side bracket bolts.

-cont.-

**NOTE** You may want to cover your rear fender to protect it from the possibility of getting scratched.

**STEP 2** Loosen the front side bracket bolt and remove the rear side bracket fastener. This will allow you to pivot the side brackets forward.

**STEP 3** Remove the four fasteners that are now holding your sissy bar in the side plates.

**STEP 4** Insert the new Raptor Bar into the side plates and secure with the four 1/4" -20 x 5/8" SHCS. It would be a good idea to use blue lock tight on these fasteners.

**STEP 5** Reinstall the two rear fasteners through the side plates that were removed in STEP 2. Tighten all four of the fasteners that secure the side plates.

**WARNING! IMPROPER INSTALLATION OR USE OF THIS PRODUCT COULD RESULT IN SERIOUS INJURY OR DEATH.**

**ATTENTION!**It is the installer's responsibility to ensure that all of the fasteners (including pre-assembled) are tightened before operation of the motorcycle. Kuryakyn will not warranty components lost due to improper installation. Periodic maintenance may be required.

*Ride On!*

**Kuryakyn®**

**PAGE**

**2**

**RAPTOR BAR INSTALLATION**