



CODICE	DIAMETRO INTERNO	PRESSIONE D'ESERCIZIO	PRESSIONE SCOPPIO	PESO NOMINALE	RAGGIO DI CURVATURA	VUOTO	LUNGHEZZA
	Mm	Bar	Bar	g/m	Mm	Bar	
480005	20	9	27	310	110	9	50
480339	25	9	27	400	175	9	50
400070	30	9	27	500	190	9	50
400061	40	9	27	760	270	9	50
400052	50	8	24	1100	350	9	50
400053	60	8	24	1450	415	9	50
480009	70	8	24	1800	480	9	50
400054	80	7	21	2200	555	9	30
400055	100	6	18	3300	695	9	30
400071	120	5	15	4200	900	9	30

For suction and delivery of non-fat food

Compliance rules: Used to wine medium heavy-duty industry according to European Directive 2007/19 / EC for simulants A - B - C.

Application: Suction and delivery hose for liquid food without fat and drinks with alcohol content up to 28 degrees.

Sanitizing: maximum 130° C for a few minutes with steam; maximum 60° C for a few minutes with acid nitric acid at 2%, 2% peracetic acid, phosphoric acid 2%, caustic soda to 5%.

Temperature: -10° C to + 50° C.

Phthalates/reach: the red spiral pipe does not contain any substances currently included in the list provided Reach legislation updated in the last available update of 19/12/2012

Structure: Flexible PVC hose with reinforcement spiral rigid anti-shock PVC. Smooth interior.