



BCS Pan Paint remover for oil paints

Is in compliance with European Parliament and Council Regulation (EC) no. 1907/2006 concerning the registration, evaluation, authorisation and restriction of chemicals (REACH)

Range of application:

BCS Pan is a efficient and highly alkaline paint remover that is developed to dissolve oil paints. Can be used on most kind of surfaces - exceptions are aluminum and magnesium.

How to use:

If the area isn't clean use a pressure-wash with hot water, you might need to use cleaning chemicals. Make sure the area is dry before applying BCS Byggver, if area has been washed leave it to dry for two days. Apply BCS Byggver with a brush, roller or paint sprayer starting at the bottom. Apply wet in wet or with one day apart. Surface may not be exposed to rain the first 2-3 hours.



Containers: 10 or 25 litre, can **Storage:** Frost-free in original packing **Dosage:** Concentrate **pH value:** 14 **Consumption:** Approx. 0,3-0,5 litre/m² **ADR:** 1719 CAUSTIC ALKALI LIQUID, N.O.S. (Caustic potash), 8, II

Precautions:

Use protective gloves made of butyl or nitrile rubber. Ensure good ventilation, avoid inhalation of dust. Use protecting clothing, gloves, visor or glasses in case of contact.

Eye wash facilities and emergency shower must be available when handling this product. For more information please see the Safety Data Sheet for this particular product.



This product information is intended only as a guideline. MPE International does not accept responsibility for the end result. If in doubt, contact MPE International for advice.

MPE International AB Dalagatan 3B S-803 10 Gävle, Sweden

Phone: +46(0)8-522 99 440 Email: info@mpei.se Web: www.mpei.se Org.nr:

556722-0420