

## **BCS Pluto**

**Paint remover**

Is in compliance with European Parliament and Council Regulation (EC) no. 1907/2006 concerning the registration, evaluation, authorisation and restriction of chemicals (REACH)

### **Range of application:**

Paint remover that removes and dissolves efficiently plastic and roof paints.

### **How to use:**

Apply on dry area with brush, roller or paint sprayer. Cover areas where the paint shouldn't be removed. Duration of action 1-48 hours depending on the thickness of the color layers. When the paint has softened, it can be removed with a putty knife, scraper or washed down with a pressure washer from the bottom up (temperature and pressure adjusted by the nature of the surface). Wash area with BCS Amor (1:20) before re-painting. Make sure there's no product left when painting.



**Containers:** 10 litre, can

**Storage:** Frost-free in original packing

**Dosage:** Concentrate

**pH value:** Neutral

**Consumption:** Approx. 0,3-2,0 litre/m<sup>2</sup>

**ADR:** Not classified as dangerous goods for use by road or rail transportation

### **Precautions:**

Use protective gloves made of butyl or nitrile rubber.

Ensure good ventilation, avoid inhalation of dust.

Use protecting clothing, gloves, visor or glasses in case of contact.

Eye wash facilities and emergency shower must be available when handling this product.

For more information please see the Safety Data Sheet for this particular product.



Signal word: Danger

This product information is intended only as a guideline. MPE International does not accept responsibility for the end result. If in doubt, contact MPE International for advice.

**MPE International AB**  
Dalagatan 3B  
S-803 10 Gävle, Sweden

**Phone:**  
+46(0)8-522 99 440

**Email:**  
info@mpei.se

**Web:**  
www.mpei.se

**Org.nr:**  
556722-0420