



MPE Boggie Cleaner

Alkaline cleaner

Area of use:

Used for degreasing and cleaning trains.

How to use:

Never apply on a hot surface and prevent drying, leave on for about 5-15 minutes. Be careful on repainted and sensitive metal and plastic surfaces. Test washing is always recommended.

Packaging: 25 liter can or 200 liter barrel
Storage: Frost-free in original packaging
pH: >14
Dosage: Dilute with water 1-25%
ADR: 1719 CAUSTIC ALKALI LIQUID, N.O.S. (Sodium hydroxide ; Caustic potash), 8, II, E

Protective equipment:

Wear tight-fitting goggles or face shield. Wear protective gloves, Butyl rubber or Nitrile. Value: 4 - 8 hour(s) Reference to relevant standard: EN 374 / III. Wear appropriate clothing to prevent any possibility of skin contact. Wear respiratory protection with combination filter (dust and gas filter) during spraying operations.

There must be access to quick and abundant eyewash in connection with the workplace. For further information and description of first aid measures see specific safety data sheet.



This product information is intended only as a guideline. MPE International does not accept responsibility for the end result. If in doubt, contact MPE International for advice.

MPE International AB Dalagatan 3B 803 10 Gävle

Phone: +46(0)8-522 99 440 E-mail: info@mpei.se

Web: Org.nr: www.mpei.se 556722-0420