

MPE Graffiti Remover 10

Gelified graffiti remover

Is in compliance with European Parliament and Council Regulation (EC) no. 1907/2006 concerning the registration, evaluation, authorisation and restriction of chemicals (REACH)

Range of application:

Gelified graffiti remover that is especially suitable for sensitive surfaces. For porous and non-porous surfaces.

How to use:

Apply with a brush, roller or high pressure and agitate the graffiti with a brush. Let the product act for about 10-30 minutes, leave it longer if thick layers of paint and if it's cold and damp weather. Always adjust the water temperature and pressure by surface conditions, normal temperature is 90°C and 90-150 bar pressure. If shadows are remaining apply OFF Tor or OFF Munin, if the surface can withstand it, and rinse.



Containers: 5 or 25 litre, can

Storage: Frost-free in original packing

Dosage: Concentrate

pH value: Neutral

Consumption: Approx. 0,3-1,0 litre/m²

ADR: Not classified as dangerous goods if transported by road or by rail

Precautions:

Use protective gloves made of butyl or nitrile rubber.

Ensure good ventilation, avoid inhalation of dust.

Use protecting clothing, gloves, visor or glasses in case of contact.

Eye wash facilities and emergency shower must be available when handling this product.

For more information please see the Safety Data Sheet for this particular product.



Signal word: Warning

This product information is intended only as a guideline. MPE International does not accept responsibility for the end result. If in doubt, contact MPE International for advice.

MPE International AB
Dalagatan 3B
S-803 10 Gävle, Sweden

Phone:
+46(0)8-522 99 440

Email:
info@mpei.se

Web:
www.mpei.se

Org.nr:
556722-0420