

## MPE Rail Cleaner

### Acid cleaner

#### Area of use:

MPE Rail Cleaner quickly and effectively cleans surfaces heavily soiled by iron oxide, dirt and air pollution.

#### How to use:

Never apply on a hot surface and prevent drying, leave on for about 5-15 minutes. Be careful on repainted and sensitive metal and plastic surfaces.



**Packaging:** 25 liter can or 200 liter barrel

**Storage:** Frost-free in original packaging

**pH-value:** Approx. 1

**Dosage:** Concentrate - 1:5

**ADR:** Not classified as dangerous goods for road or rail transport.

#### Protective equipment:

Provide adequate ventilation. Wear tight-fitting goggles or face shield. Protective gloves are recommended. Butyl rubber. Nitrile. Value: 4 ~ 8 hour(s) Reference to relevant standard: EN 374/III. Wear appropriate clothing to prevent any possibility of skin contact. Respiratory protection must be used if air contamination exceeds acceptable level. Wear respiratory protection with combination filter (dust and gas filter) during spraying operations. Wear respiratory protection. A2/P3.

There must be access to quick and abundant eyewash in connection with the workplace. For further information and description of first aid measures see specific safety data sheet.



Signal word: Danger

This product information is intended only as a guideline. MPE International does not accept responsibility for the end result. If in doubt, contact MPE International for advice.