



OFF Ask Graffiti protection

Approved by BASTA, Byggvarubedömningen, Sunda Hus, Chemsoft and Trafikverket

Range of application:

OFF Ask, wax based diffusion-open graffiti protection, which is very effective against graffiti. OFF Ask is approved according to AMA 20.

How to use:

Dirty surfaces should be cleaned before application, for example, with BCS Amor. Apply OFF Ask with a roller, a low pressure spray or a paint sprayer. Depending on the porosity of the surface, 2-3 layers of graffiti protection may be required. Apply until the surface is saturated, the graffiti protection must be surface dry before subsequent coats are applied. Always apply to a test area to detect any colour differences. Clean the sprayer with water following application.

If the underlying surface withstands high pressure and hot water, remove the graffiti at 80-90°C and 120-200 bar. In difficult to clean cases and sensitive surfaces, OFF Iris can be applied and let sit for 5 minutes, then washed with appropriate pressure and temperature.

Containers: 10 or 25 litre, can Storage: Frost-free in original packing Shelf life: 12 months at room temperature in unopened packaging. Dosage: Concentrate pH value: Neutral Consumption: Approx. 0,1-0,4 litre/m² ADR: Not classified as dangerous goods for use by road or rail transportation

Precautions:

Ensure good ventilation. Irritates eyes and skin. Use protective clothing, gloves and glasses or visor in risk of contact

Eye wash facilities and emergency shower must be available when handling this product. For more information please see the Safety Data Sheet for this particular product.

This product information is intended only as a guideline. MPE International does not accept responsibility for the end result. If in doubt, contact MPE International for advice.

MPE International AB
Dalagatan 3BPhone:Email:Web:Org.nr:+46(0)8-522 99 440info@mpei.sewww.mpei.se556722-0420S-803 10 Gävle, Sweden