

OFF Askgård

Graffiti protection

Approved by Bygghälsömyndigheten, Sunda Hus, Chemsoft and Trafikverket

Range of application:

Permanent one-component graffiti protection, suitable for "dead areas" such as sheet metal, aluminium, etc. Common items that can be protected by OFF Askgård include: Electrical cabinets, lamp-posts and litter bins.

How to use:

Clean surfaces from graffiti, dirt, soot and other pollutants before you apply OFF Askgård. Apply with a paint pad, paint brush or paint sprayer depending on surface material. Allow the first coat to dry (approx. 2 hours) before subsequent coats are applied. Best results are obtained at temperature of +5° to +30°C
SPS Isis and Graffiti remover 2 are appropriate products to sanitize with on OFF Askgård.




Containers: 5 or 25 litre, can
Storage: Frost-free in original packing
Dosage: Concentrate
pH value: Neutral
Consumption: Approx. 0,1-0,3 litre/m²
ADR: UN 1263 PAINT, 3, III, (D/E)

Precautions:

Use protective gloves made of butyl or nitrile rubber.
Ensure good ventilation, avoid inhalation of dust.
Use protecting clothing, gloves, visor or glasses in case of contact.

Eye wash facilities and emergency shower must be available when handling this product.
For more information please see the Safety Data Sheet for this particular product.



Signal word: Danger

This product information is intended only as a guideline. MPE International does not accept responsibility for the end result.
If in doubt, contact MPE International for advice.