

## OFF Ask Ice

**Graffiti protection for porous surfaces, suitable for low temperatures**

Follows EU's directive for detergents

### Range of application:

Strong diffusion opened graffiti protection, suitable for porous surfaces. OFF Ask winter is suitable for many surfaces and may be applied down to a temperature of around - 5°C.

### How to use:

Contaminated surfaces are cleaned before graffiti protection is applied. It is preferable to clean with SPS Isis for example. Apply Off Ask with a low pressure or paint sprayer. Depending on the porosity of the surface 2-3 layers graffiti protection are applied. Apply until the surface is saturated, the graffiti protection needs to be dry before another layer is applied.

If the underlying surface withstands high pressure and hot water, remove the graffiti at 80-90°C and 120-200 bar. In difficult to clean cases and sensitive surfaces, OFF Iris can be applied and let sit for 5 minutes, then washed with appropriate pressure and temperature.



**Containers:** 10 or 25 litre, can

**Storage:** Frost-free in original packing

**Dosage:** Concentrate

**pH value:** Neutral

**Consumption:** Approx. 0,2-0,4 litre/m<sup>2</sup>

**ADR:** 1992 FLAMMABLE LIQUID, N.O.S. (Propan-2-ol), 3, III, D/E

### Precautions:

Wear approved chemical safety goggles where eye exposure is reasonably probable. Skin- / hand protection, short term contact - Hand protection not required. Skin- / hand protection, long term contact - Protective gloves are recommended. Butyl rubber. Nitrile. Reference to relevant standard: EN 374/III. Wear appropriate clothing to prevent reasonably probable skin contact. Respiratory protection must be used if air contamination exceeds acceptable level. A2. Wear respiratory protection with combination filter (dust and gas filter) during spraying operations.

Eye wash facilities and emergency shower must be available when handling this product.  
For more information please see the Safety Data Sheet for this particular product.



Signal word: Warning

This product information is intended only as a guideline. MPE International does not accept responsibility for the end result.  
If in doubt, contact MPE International for advice.

**MPE International AB**  
Dalagatan 3B  
S-803 10 Gävle, Sweden

**Phone:**  
+46(0)8-522 99 440

**Email:**  
info@mpei.se

**Web:**  
www.mpei.se

**Org.nr:**  
556722-0420