

OFF Ask One Layer

Graffiti protection

Approved by BASTA, Byggvarubedömningen, Sunda Hus, Chemsoft and Trafikverket

Range of application:

OFF Ask One Layer is a wax based diffusion-open graffiti protection, which is very effective against graffiti. OFF Ask One Layer is approved according to AMA 20.

How to use:

Dirty surfaces should be cleaned before application, for example, with BCS Amor. Apply OFF Ask Enlager with a roller, a low pressure spray or paint sprayer. It is sufficient to apply one coat until the surface is saturated. It's easy and it's fast to remove graffiti on OFF Ask Enlager. Always apply to a test area to detect any colour differences. Clean the sprayer with water following application.

If the underlying surface withstands high pressure and hot water, remove the graffiti at 80-90°C and 120-200 bar. In difficult to clean cases and sensitive surfaces, OFF Iris can be applied and let sit for 5 minutes, then washed with appropriate pressure and temperature.



Containers: 10 or 25 litre, can

Storage: Frost-free in original packing

Shelf life: 12 months at room temperature in unopened packaging.

Dosage: Concentrate

pH value: Neutral

Consumption: Approx. 0,1-0,4 litre/m²

ADR: Not classified as dangerous goods for use by road or rail transportation

Test reports: Listed in The House Product Portal for your building to be Nordic Swan Ecolabelled, AMA-20

Precautions:

Ensure good ventilation. Irritates eyes and skin.

Use protective clothing, gloves and glasses or visor in risk of contact

Eye wash facilities and emergency shower must be available when handling this product.

For more information please see the Safety Data Sheet for this particular product.

This product information is intended only as a guideline. MPE International does not accept responsibility for the end result.
If in doubt, contact MPE International for advice.

MPE International AB
Dalagatan 3B
S-803 10 Gävle, Sweden

Phone:
+46(0)8-522 99 440

Email:
info@mpei.se

Web:
www.mpei.se

Org.nr:
556722-0420