

OFF Graffiti Remover Eco+ Gel

Thickened graffiti remover, labelled with Good Environmental Choice

Area of application:

OFF Graffiti Remover Eco+ Gel is a highly effective gel-based graffiti remover that efficiently dissolves graffiti. Can be used on most surfaces – always carry out a test on a small area first.

Work instructions:

For interior graffiti removal in vehicles:

Apply OFF Graffiti Remover Eco with a cloth or brush and work the graffiti using a cleaning sponge or brush until the graffiti is dissolved. Then wipe the surface clean with a clean cloth and rinse with water.

Dwell time on painted surfaces: 5–30 minutes. Repeat the process if necessary.

For exterior graffiti removal on vehicles:

Apply OFF Graffiti Remover Eco+ Gel with a brush and work the graffiti until it is dissolved. Then wash off the graffiti using high-pressure washing. Adjust pressure and temperature so that the underlying surface is not damaged. Repeat the treatment if necessary.

Dwell time on painted surfaces: 5–30 minutes.

For graffiti removal on porous surfaces:

Apply with a brush, roller or high-pressure sprayer and work the graffiti with a brush. Dwell time approx. 10–30 minutes. Allow longer dwell time for thick paint layers and in cold or humid weather conditions. Always adjust water temperature and pressure according to the type of surface; under normal conditions rinsing is carried out at 90 °C and 90–150 bar pressure. If shadowing remains, apply OFF Tor or OFF Munin if the substrate can tolerate it, then rinse off. Always test on a small area to ensure that the underlying surface is not damaged.

Packaging: 10 or 25 litres, jerry can

Storage: Frost-free, in original packaging

Dosage: Concentrate

pH: Neutral

Consumption: Non-porous surfaces approx. 0.2–0.4 L/m², porous surfaces approx. 0.3–0.75 L/m²

ADR: Not classified as dangerous goods for road and rail transport

Personal Protective Equipment:

Respiratory protection must be used when airborne contamination exceeds the occupational exposure limit, and during spraying, in which case a combination filter (dust and gas filter) must be used. Hand protection must be used for exposure of 4–8 hours; protective gloves made of butyl or nitrile rubber are recommended. Eye and skin protection should be used when there is a risk of splashing.

There must be access to quick and ample eye rinsing facilities in close proximity to the workplace.

For further information and instructions on first aid measures, please refer to the specific safety data sheet.



Signal Word: Warning

Good Environmental Choice

This product information is intended as guidance only. MPE International accepts no responsibility for the final result. If in doubt, contact MPE International for advice. Think of the environment: do not use more than necessary.