

OFF Hugin

Gel graffiti remover

Approved by Byggarbetsnämningen, Sunda Hus, Chemsoft and Trafikverket

Range of application:

Suitable for external graffiti removal on trains and other hard surfaces that can withstand high pressure cleaning. OFF Hugin also works on porous surfaces.

How to use:

Apply with a brush, roller or high-pressure spray and agitate the graffiti with a brush. It takes effect after approx. 5-30 minutes. Allow longer for thick paint layers as well as in cold and damp weather. Always adjust the water temperature and pressure to the type of surface. Apply a temperature/pressure of 90°C / 90-150 bar if the area being cleaned can withstand such. If there are remaining shadows, apply shadow remover OFF Tor or OFF Munin if the surface can withstand this, and then rinse off.



Containers: 10 litre, bucket

Storage: Frost-free in original packing

Dosage: Concentrate

pH value: 12,5

Consumption: Approx. 0,3-1,0 litre/m²

ADR: Not classified as dangerous goods if transported by road or by rail

Precautions:

Use protective gloves made of butyl or nitrile rubber.

Ensure good ventilation, avoid inhalation of dust.

Use protecting clothing, gloves, visor or glasses in case of contact.

Eye wash facilities and emergency shower must be available when handling this product.

For more information please see the Safety Data Sheet for this particular product.



Signal word: Warning

This product information is intended only as a guideline. MPE International does not accept responsibility for the end result. If in doubt, contact MPE International for advice.

MPE International AB
Dalagatan 3B
S-803 10 Gävle, Sweden

Phone:
+46(0)8-522 99 440

Email:
info@mpei.se

Web:
www.mpei.se

Org.nr:
556722-0420