

OFF Lin

Starch-based graffiti protection

Range of application:

An environmentally friendly starch-based graffiti protection that can be applied to most types of absorbent substrate. OFF Lin prevents severe graffiti shadows. Recommended for statues and K-marked facades as the product is completely invisible, but gives the surface the necessary protection. Diffusion open graffiti protection. UV resistant. Estimated life span approx. 4 years.

How to apply:

First, the surface must be thoroughly cleaned from graffiti and other contaminants such as traffic dirt, wax, oil, paint residue, etc. Mask or protect window glass appropriately. Allow the surface to dry so that it is completely dry or slightly moist, but not wet. NOTE! New concrete must burn at least 28 days before OFF Lin is applied. Let newly painted surfaces dry for 1-4 weeks depending on the paint type, before applying OFF Lin. Shake or stir the product well before use!

Apply OFF Lin with roller or paint sprayer. OFF Lin should be applied in 2-3 layers and the first layer should be surface dry before the next layer is applied (30 minutes - 1 hour normally). The surface must have a minimum temperature of 5°C. Drying time is 1-3 hours, depending on temperature and humidity. After treatment, it is easier to remove graffiti or other unwanted contaminations.

Use high-pressure (60-130 bar) and hot water (about 65°C). Adjust the pressure to the facade nature.

How to remove graffiti from OFF Lin:

Method 1

Normal porous surfaces

Remove graffiti with high pressure (60-130 bar) and hot water (approx. 60°C), adjust pressure and temperature to surface condition.

In severe cases apply OFF Graffiti Remover Eco or OFF Graffiti Remover Eco Gel, let sit for about 10 min. Carefully work with a brush and then wash it with appropriate pressure and temperature.

Apply OFF Lin again, 2-3 layers.

Method 2

Sensitive surfaces, painted surfaces

Apply OFF Graffiti Remover Eco and let sit for about 5 minutes. Carefully work with brush, then rinse with appropriate pressure and temperature. Smaller pieces of graffiti can be removed with OFF Graffiti Remover Eco and a cloth.



Containers: 25 litre, can

Storage: Frost-free in original packing

Dosage: Concentrate

pH value: Neutral

Consumption: Approx. 0,1-0,4 litre/m²

ADR: Not classified as dangerous goods if transported by road or by rail

Test reports: Listed in The House Product Portal for your building to be Nordic Swan Ecolabelled, AMA-20

Precautions:

Ensure good ventilation. Irritates eyes and skin.

Use protective clothing, gloves and glasses or visor in risk of contact

Eye wash facilities and emergency shower must be available when handling this product.

For more information please see the Safety Data Sheet for this particular product.

This product information is intended only as a guideline. MPE International does not accept responsibility for the end result.

If in doubt, contact MPE International for advice.



MPE International AB
Dalagatan 3B
S-803 10 Gävle, Sweden

Phone:
+46(0)8-522 99 440

Email:
info@mpei.se

Web:
www.mpei.se

Org.nr:
556722-0420