

OFF Loke Power

Efficient gel graffiti remover

Is in compliance with European Parliament and Council Regulation (EC) no. 1907/2006 concerning the registration, evaluation, authorisation and restriction of chemicals (REACH)

Range of application::

An efficient all-round graffiti remover. OFF Loke Power is in first hand developed for porous surfaces with graffiti that is hard to remove. It has also been tested on trains with very good results.

How to use:

Apply product with a rag or a brush on hard non-porous surfaces. Agitate the graffiti with a sponge or a brush until it's dissolved; wipe off the dissolved graffiti with a clean rag or rinse with water if possible.

On porous surfaces the product is applied with a roller or a brush. Let the product act for 10-30 minutes, or as long as is needed. Jet off the dissolved graffiti and adjust the pressure and temperature by the nature of the surface. Normally you jet off with water 90°C and a pressure of 90 -150 bars. Rinse off immediately after application with water or window cleaner. Apply OFF Loke Power with a cloth or a brush and agitate the surface with a cloth or a sponge.



Containers: 10 or 25 litre, can
Storage: Frost-free in original packing
Dosage: Concentrate
pH value: 13
Consumption: Approx. 0,1-0,3 litre/m²
ADR: UN 1993 FLAMMABLE LIQUID, N.O.S., 3, III

Precautions:

Use protective clothing, gloves and glasses or visor.
Ensure good ventilation. Irritates eyes and skin.

Eye wash facilities and emergency shower must be available when handling this product.
For more information please see the Safety Data Sheet for this particular product.



Signal word: Warning

This product information is intended only as a guideline. MPE International does not accept responsibility for the end result.
If in doubt, contact MPE International for advice.

MPE International AB
Dalagatan 3B
S-803 10 Gävle, Sweden

Phone:
+46(0)8-522 99 440

Email:
info@mpei.se

Web:
www.mpei.se

Org.nr:
556722-0420