

OFF Oden+

Thickened graffiti remover, suitable for low temperatures

Follows EU's directive for detergents

Range of application:

Gelified graffiti remover for porous and non-porous surfaces. Adapted to low temperatures.

How to use:

Apply with a brush, roller or high pressure nozzle; agitate the surface with a brush. Time of action 10-30 minutes, thick paint layering or cold or humid weather conditions increases the time of action. Adjust temperature and pressure by the nature of the surface. Normally you jet off with water 90°C and a pressure of 90-150 bars. If shadows remain, apply shadow removers OFF Tor or OFF Munin and jet off again.



Containers: 10 or 25 litre, can

Storage: Frost-free in original packing

Dosage: Concentrate

pH value: Neutral

Consumption: Approx. 0,4-1,0 litre/m²

ADR: UN 1993, FLAMMABLE LIQUID, N.O.S. (Solvent naphtha (petroleum), light arom.), 3, III

Precautions:

Use protective clothing, gloves and glasses or visor.

Ensure good ventilation. Repeated skin contact may give dry skin and skin crackings.

Eye wash facilities and emergency shower must be available when handling this product.

For more information please see the Safety Data Sheet for this particular product.



Signal word: Warning

This product information is intended only as a guideline. MPE International does not accept responsibility for the end result. If in doubt, contact MPE International for advice.

MPE International AB
Dalagatan 3B
S-803 10 Gävle, Sweden

Phone:
+46(0)8-522 99 440

Email:
info@mpei.se

Web:
www.mpei.se

Org.nr:
556722-0420