

- for a cleaner world -

MPE
INTERNATIONAL®

- for a cleaner world -

OFF
ANTI GRAFFITI SYSTEM

OFF Shadow Remover Eco

Alkaline shadow remover

Range of application:

Used on remaining shadows.

NOTE! Should not be used on aluminum. Use with caution on painted surfaces.

How to use:

Apply with brush or roller and work into the surface. Allow to take effect, approx. 5-20 min. Allow to take effect longer if old or hard shadows, and at lower temperatures. A suitable water temperature and pressure would normally be 90°C and 90-150 bar pressure, depending on the surface type. For any remaining shadows, apply MPE Shadow Remover again and allow to take effect until all graffiti is dissolved. Rinse off.

Containers: 5 or 25 litre, can

Storage: Frost-free in original packing

Dosage: Concentrate

pH value: 14

Consumption: Non-porous surface 0,10-0,15 L/m², porous surface 0,20-0,35 L/m²

ADR: 1719 CAUSTIC ALKALI LIQUID, N.O.S. (Caustic potash), 8, II, (E)

Precautions:

Use protective gloves made of butyl or nitrile rubber.

Ensure good ventilation, avoid inhalation of dust.

Use protecting clothing, gloves, visor or glasses in case of contact.

Eye wash facilities and emergency shower must be available when handling this product. For more information please see the Safety Data Sheet for this particular product.



Bra Miljöval

GREEN
LINE



Signal word: Danger

This product information is intended only as a guideline. MPE International does not accept responsibility for the end result. If in doubt, contact MPE International for advice.

Issued:
11/11/2020

MPE International AB
Dalagatan 3B
S-803 10 Gävle, Sweden

Phone:
+46(0)8-522 99 440

Email:
info@mpei.se

Web:
mpei.se/en

Org.nr:
556722-0420