

OFF Tyr Tixo

Shadow remover

Approved by Bygghälsöförmyndningen, Sunda Hus, Chemsoft and Trafikverket

Range of application:

OFF Tyr Tixo is a thixotropic product used for bleaching remaining shadows. NOTE! the product may not be used on aluminum, copper, zinc or galvanized surfaces. Always try out first to ensure the substrate can withstand the product.

How to use:

Apply Off Tyr Tixo with a brush to the surface to be cleaned. If it takes a long time to take effect, wrap plastic around the surfaces to be treated. Cover surfaces that are not to be cleaned. Apply 0.5-1.1/m², allow to take effect 0.5 – 12 hours. Rinse with lukewarm water.



Containers: 5 litre, can
Storage: Frost-free in original packing
Dosage: Concentrate
pH value: 11,5
Consumption: Approx. 0,1-0,3 litre/m²
ADR: UN 1791 HYPOCHLORITE SOLUTION, 8, II

Precautions:

Use protective gloves made of butyl or nitrile rubber.
Ensure good ventilation, avoid inhalation of dust.
Use protecting clothing, gloves, visor or glasses in case of contact.

Eye wash facilities and emergency shower must be available when handling this product.
For more information please see the Safety Data Sheet for this particular product.



Signal word: Danger

This product information is intended only as a guideline. MPE International does not accept responsibility for the end result.
If in doubt, contact MPE International for advice.