

SPS Greenclean Facade

Facade and special cleaning

Area of use:

MPE Greenclean Facade can be applied with a foam sprayer, which provides a longer working time and more efficient cleaning. Maintenance washing for facades, cleaning in industries and fire remediation. MPE Greenclean Facade is an alkaline product that effectively dissolves greasy dirt such as traffic exhaust gases and air pollution, and is effective in washing away growth such as algae.

How to use:

Wet the surface with water and apply diluted MPE Greenclean Facade to a limited area. Use a low-pressure sprayer, brush or sponge. Leave on for up to 10 minutes and then process the surface with a brush or sponge, repeat washing if necessary. Work from the bottom to avoid streaks of runny detergent. High pressure washing can be used, but should be avoided if the surface can be damaged. Adjust the pressure according to the nature of the surface, maximum temperature is 50°C. Wash from the bottom up and rinse from the top down.

Containers: 10 or 25 litre, can

Storage: Frost-free in original packing

Dosage: 1:2 - 1:20

Consumption: Approx. 0,1 – 0,3 liter/m²

pH value: 12,4

ADR: CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (Caustic potash), 8, III, E

Precautions:

Wear protective gloves. Butyl rubber. Nitrile. Respiratory protection must be used if air contamination exceeds acceptable level. A2/P3

Eye wash facilities and emergency shower must be available when handling this product. For more information please see the Safety Data Sheet for this particular product.



Good Environmental Choice



Signal word: Danger

This product information is intended only as a guideline. MPE International does not accept responsibility for the end result. If in doubt, contact MPE International for advice.

Issued:
19/06/2023

MPE International AB
Dalagatan 3B
803 10 Gävle

Phone:
+46(0)8-522 99 440

Mail:
info@mpei.se

Web:
www.mpei.se

Org.nr:
556722-0420

- for a cleaner world -