

SPS Låga

Cleaning and fire restoration

Is in compliance with European Parliament and Council Regulation (EC) no. 1907/2006 concerning the registration, evaluation, authorisation and restriction of chemicals (REACH)

Range of application:

A concentrated product that efficiently dissolves soot, animal and vegetable fat.
NOTE! Can damage aluminum and galvanized surfaces. May not dry on glass.

How to use:

Applied with advantage in low-pressure spray on surface to be cleaned. Leave for 2-10 minutes. Mechanical treatment increases the cleaning effect. Rinse with water.



Containers: 10 or 25 litre, can

Storage: Frost-free in original packing

Dosage: Concentrate

pH value: 14

Consumption: Approx. 0,1-0,3 litre/m²

ADR: UN3267 CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (Caustic potash, Glutamic acid, N,Ndiacetic acid, tetrasodium salt), 8, II, (E)

Precautions:

Use protective gloves made of butyl or nitrile rubber.
Ensure good ventilation.
Use protecting clothing, gloves, visor or glasses in case of contact.

Eye wash facilities and emergency shower must be available when handling this product.
For more information please see the Safety Data Sheet for this particular product.



Signal word: Danger

This product information is intended only as a guideline. MPE International does not accept responsibility for the end result.
If in doubt, contact MPE International for advice.

MPE International AB
Dalagatan 3B
S-803 10 Gävle, Sweden

Phone:
+46(0)8-522 99 440

Email:
info@mpei.se

Web:
www.mpei.se

Org.nr:
556722-0420