

## SPS Loke

Efficient graffiti remover

Approved by Byggarbetsnämningen, Sunda Hus, Chemsoft and Trafikverket

### Range of application:

SPS Loke is a thin liquid graffiti remover especially developed to be used on porous and non-porous surfaces.

### How to use:

SPS Loke is applied with a rag or a brush on hard non-porous surfaces. Agitate the graffiti with a sponge or a brush until it's dissolved; wipe off the dissolved graffiti with a clean rag or rinse with water if possible.

On porous surfaces the product is applied with a roller or a brush. Let the product act for 10-30 minutes, or as long as is needed. Jet off the dissolved graffiti and adjust the pressure and temperature by the nature of the surface. Normally you jet off with water 90°C and a pressure of 90 -150 bars. Rinse off immediately after application with water or window cleaner. Apply SPS Loke with a cloth or a brush and agitate the surface with a cloth or a sponge.



**Containers:** 10 or 25 litre, can

**Storage:** Frost-free in original packing

**Dosage:** Concentrate

**pH value:** 13

**Consumption:** Approx. 0,1-0,3 litre/m<sup>2</sup>

**ADR:** UN 2920 CORROSIVE LIQUID, FLAMMABLE, N.O.S. (Caustic potash, Distillates (petroleum), hydrotreated light), 8(3), II, D/E

### Precautions:

Use protective clothing, gloves and glasses or visor.

Ensure good ventilation. Irritates eyes and skin.

Eye wash facilities and emergency shower must be available when handling this product.

For more information please see the Safety Data Sheet for this particular product.



Signal word: Danger

This product information is intended only as a guideline. MPE International does not accept responsibility for the end result. If in doubt, contact MPE International for advice.

**MPE International AB**  
Dalagatan 3B  
S-803 10 Gävle, Sweden

**Phone:**  
+46(0)8-522 99 440

**Email:**  
info@mpei.se

**Web:**  
www.mpei.se

**Org.nr:**  
556722-0420