

Care and Maintenance

Glass doors & glass walls

For all combinations of glass doors and glass walls for indoor use, with 6 or 8 mm toughened safety glass, both clear and patterned.

Products	Glass doors and glass walls in all combinations
Profiles and finish	Powder-coated aluminium
Glass	6 or 8 mm toughened safety glass, clear or patterned
Scope	Care and use of installed glass sections

Daily use

Open and close the door gently using the handle. Keep the door's path clear and avoid slamming it. Do not force the door if it sticks or catches on the floor or frame.

Avoid impacts to the glass in doors and walls, especially at edges and corners. Do not hang objects from glass sections, door leaves or handles. Make sure the door cannot strike a wall, furniture or other hard objects.

Cleaning clear and patterned glass

First remove loose dust and grit carefully with a damp, soft, clean cloth. Wash with lukewarm water and a small amount of mild, pH-neutral, non-abrasive cleaner.

For patterned glass, clean along the lines of the pattern. If dirt is trapped in a textured surface, carefully use a soft brush. Wipe away the cleaner with a cloth dampened with clean water and finish with a soft, lint-free cloth. Do not let water collect in profiles or fittings.

Do not use razor blades, metal scrapers, steel wool, scouring pads or abrasive cleaners. Do not work on stains with hard tools. Contact Nooli Living if stains cannot be removed with gentle cleaning.

An alternative cleaning method using diluted vinegar is described on the next page.

Cleaning & material care

Mild vinegar cleaning mixture

For the glass surface. If the glass has a special surface treatment or coating, check the supplier's instructions first. Vinegar is not suitable for every coating.

Mix 1 part 12% vinegar with 8-10 parts lukewarm water.

Example: 100 ml vinegar + 800-1,000 ml water.

First wipe away dust and loose particles with a clean, soft microfibre cloth.

Spray the mixture **onto the microfibre cloth** rather than directly onto the glass. This reduces the risk of liquid running into profiles, trim or fittings.

Wipe the entire glass surface carefully. On patterned glass, wipe along the lines of the pattern. Avoid heavy pressure.

For stains or limescale, leave the surface damp for **1-2 minutes**, but do not allow the solution to dry.

Then wipe with a clean cloth dampened with plain water. Finish with a dry, clean microfibre cloth to avoid streaks.

Important: Do not use scouring pads, razor blades, abrasive cleaners or strong chemicals. Keep the vinegar mixture away from profiles, trim and fittings.

Cleaning powder-coated aluminium

Wipe profiles and handles with a soft cloth, lukewarm water and a mild, pH-neutral cleaner. Wipe again with a cloth dampened with clean water, then dry thoroughly.

Avoid solvents, strong acids or alkaline products, abrasives and polishes. Do not use a pressure washer or steam cleaner. Always test a new cleaner on a small, inconspicuous area first.

Contact and documentation

Nooli Living

info@nooliliving.se | 044-22 35 50

www.nooliliving.se