


































Corrections to the book "VRF Communications"

Edition 1, 2021

PAGE	CORRECTION										
37	The way braking action is reported have changed. Friction and common terms are not used anymore. Instead, a common runway condition code (RWYCC) is used. It ranges from 6 to 1, where 6 is a dry runway with optimum braking action, and where 1 is poor and icy. Phraseology is changed to RUNWAY ZERO THREE, SURFACE CONDITION CODE FIVE, FIVE, FOUR.										
43	In exercise 3.2 the clearance is read in the incorrect order. The correct order is seen below: <table border="1" data-bbox="391 1019 1308 1243"> <tr> <td></td> <td>Sierra India Alpha, request taxi</td> </tr> <tr> <td></td> <td>Sierra India Alpha, taxi to holding point runway zero five via Alpha</td> </tr> <tr> <td></td> <td>Taxi to holding point runway zero five via Alpha, Sierra India Alpha</td> </tr> </table>		Sierra India Alpha, request taxi		Sierra India Alpha, taxi to holding point runway zero five via Alpha		Taxi to holding point runway zero five via Alpha, Sierra India Alpha				
	Sierra India Alpha, request taxi										
	Sierra India Alpha, taxi to holding point runway zero five via Alpha										
	Taxi to holding point runway zero five via Alpha, Sierra India Alpha										
46	In exercise 3.10, the word TO shall precede clearance to altitude. See below: <table border="1" data-bbox="391 1294 1308 1675"> <tr> <td></td> <td>Jönköping Tower, Sierra Echo Mike India Alpha</td> </tr> <tr> <td></td> <td>Sierra Echo Mike India Alpha, Jönköping Tower</td> </tr> <tr> <td></td> <td>Sierra Echo Mike India Alpha, on flightplan to Jönköping, just south east of Jönköping TMA, three thousand five hundred feet, squawking five three four one, to land</td> </tr> <tr> <td></td> <td>Sierra India Alpha, roger. Cleared to Hyltena. When ready descend to two thousand two hundred feet. QNH one thousand</td> </tr> <tr> <td></td> <td>Cleared to Hyltena. When ready descend to two thousand two hundred feet. QNH one thousand, Sierra India Alpha</td> </tr> </table>		Jönköping Tower, Sierra Echo Mike India Alpha		Sierra Echo Mike India Alpha, Jönköping Tower		Sierra Echo Mike India Alpha, on flightplan to Jönköping, just south east of Jönköping TMA, three thousand five hundred feet, squawking five three four one, to land		Sierra India Alpha, roger. Cleared to Hyltena. When ready descend to two thousand two hundred feet. QNH one thousand		Cleared to Hyltena. When ready descend to two thousand two hundred feet. QNH one thousand, Sierra India Alpha
	Jönköping Tower, Sierra Echo Mike India Alpha										
	Sierra Echo Mike India Alpha, Jönköping Tower										
	Sierra Echo Mike India Alpha, on flightplan to Jönköping, just south east of Jönköping TMA, three thousand five hundred feet, squawking five three four one, to land										
	Sierra India Alpha, roger. Cleared to Hyltena. When ready descend to two thousand two hundred feet. QNH one thousand										
	Cleared to Hyltena. When ready descend to two thousand two hundred feet. QNH one thousand, Sierra India Alpha										
49	In exercise 3.17 the word TO shall precede an intention to climb or descend to an altitude. See below: <table border="1" data-bbox="391 1758 1308 2004"> <tr> <td></td> <td>Sierra Lima Oscar, traffic, a Piper PA28 one five miles south of the field, proceeding to position overhead, two thousand five hundred feet, to land</td> </tr> <tr> <td></td> <td>Roger. Lining up runway two eight via backtrack. Intention after departure to climb straight ahead to three thousand feet to Delta Kilo followed by right turn to the town of Vilhelmina, Sierra Lima Oscar</td> </tr> <tr> <td></td> <td>Sierra Lima Oscar, roger</td> </tr> </table>		Sierra Lima Oscar, traffic, a Piper PA28 one five miles south of the field, proceeding to position overhead, two thousand five hundred feet, to land		Roger. Lining up runway two eight via backtrack. Intention after departure to climb straight ahead to three thousand feet to Delta Kilo followed by right turn to the town of Vilhelmina, Sierra Lima Oscar		Sierra Lima Oscar, roger				
	Sierra Lima Oscar, traffic, a Piper PA28 one five miles south of the field, proceeding to position overhead, two thousand five hundred feet, to land										
	Roger. Lining up runway two eight via backtrack. Intention after departure to climb straight ahead to three thousand feet to Delta Kilo followed by right turn to the town of Vilhelmina, Sierra Lima Oscar										
	Sierra Lima Oscar, roger										
56	In 3.31 the pilot uses an abbreviated call sign before ATC has done so, which is not allowed. Call sign should be read in full until each new ATS unit has used the abbreviated call sign for the first time.										