

# TECHNICAL DATASHEET

## FLOOR SOFT SOAP (GOLVSÅPA)

Selder & Company AB 7.5.2021

[www.selder.com/en](http://www.selder.com/en)

Linseed oil soap for soap treating wooden floors.



When treating wooden floors with FLOOR SOFT SOAP, a protective layer of soap is formed. It gradually dissolves as the floor is wiped off with water. One soap treatment is sufficient for 30-50 wipes. The floor is gradually bleached as you wipe it. Oak is bleached particularly strongly because the oxalic acid in the wood reacts with the soap. This forms a dark brown to black surface, which is washed off with water.

### Work manual

Apply FLOOR SOFT SOAP with a wide brush. Move from places that are saturated to places that still absorb soap. Continue until the entire surface is saturated, then remove the excess. When the surface is completely dry, you can polish or wet swipe with cold water. When it starts to get difficult to remove dirt with cold water, scrub the floor clean and let it dry, then repeat the soap treatment.

NOTE: FLOOR SOFT SOAP dissolves linseed oil paint and attacks aluminium.

### WORKER PROTECTION

The soap dries out the skin. Wear gloves when working with the soap. Protect your eyes, as the soap is a potent irritant.

Visit our website at [www.selder.com/en](http://www.selder.com/en) for more information.

**Contains:** Linseed oil soap 50 % vol., water 50 % vol.

**Consumption:** 1-2 dl/m<sup>2</sup>.

**Packaging:** 1 and 5 litre cans.

Selder & Company AB  
Knivstagatan 11  
75323 Uppsala,  
Sweden  
+46 73 0700 384

