

Wallpapering with QuickUp wallpaper

1. When applying a QuickUp wallpaper (Non-Woven), paste is applied directly onto the wall over an area equivalent to the width of 2-3 lengths (approx. 1-1.5 m). Use a brush on areas that are hard to reach.

2. Start from a door, window or corner. When you arrive at switches and sockets, turn off the power and undo the sockets. Cut the wallpaper to fit while it's damp before putting switches and sockets back.

3. Place the roll in the QuickUp box (tray) and pull up the first length. Hang it gently in position, high enough up to allow a small part of the length to project over the cornice (or similar) where you plan to cut the paper to fit. Check that the length is vertical using scissors hanging from a string, for example. Lift the wallpaper if it's not straight. Don't try to turn it. Bubbles may form if there's no paste on one area or if the underlying wallpaper has come away from the wall. In this case, carefully lift the wallpaper and brush more paste onto the wall.

4. Smooth out the wallpaper from the centre using the wallpaper smoothing tool, moving outwards to remove the air bubbles. Take care at the edges so that you don't get paste on the tool or the wallpaper. Quickly wipe away any paste on the front of the wallpaper using a sponge and clean water.

5. Allow the wallpaper to extend a few millimetres beyond the edges (floor and ceiling), then cut the wallpaper cleanly. Replace your knife blades frequently as a blunt blade will tear your wallpaper.

6. Put up the next length, edge to edge (don't overlap the lengths). Make sure you align the pattern correctly to achieve the best results.

7. Lengths are cut lengthwise at corners. Paste just over one length around the corner. Allow the first part of the length to go 2 cm around the corner.



– Is it an inner corner?

Put up the next length with an overlap into the corner, apply paste to the part of the wallpaper beneath the overlap. Wipe away any excess paste using the sponge.

– Is it an outer corner?

Place the next length approx. 5 mm across onto the next wall to prevent it being pulled up if anyone brushes against it. Wipe away any excess paste using the sponge.

8. Air the room thoroughly. Wallpapers dry best at normal room temperature. Note: Non-woven material is permeable to moisture. Areas of moisture occurring during wallpapering will disappear when the wallpaper has dried (normally within 24 hours).