

TIG200PACDC PFC



Features:

- Rugged, robust, and industrial look with ergonomic design
- **ClearVision** Technology
- Adaptable wide voltage range
- HF stabilizing technology
- **Dash-Arc**
- **Smart Lift TIG**
- Full-featured pulse TIG parameters
- Multiple AC waveforms
- Mixed waveform, mixed waveform frequency, mixed wave duty cycle
- Flexible remote control solutions
- Power factor correction (PFC), generator-friendly
- Quick factory reset; auto sleep mode
- Water cooled option available
- **ABAP: Active Balancing Air Passage**
- **Smart gas** for optimized shielding gas consumption
- On demand fan
- Voltage Reduction Device (VRD)
- Key power electronic component protection
- Overcurrent and overheat protection



SISAB
SVETS & VERKTYGSGRÖSSISTEN SINCE 1987

Specifikationer:

		TIG200P ACDC PFC E2S22	
Ingångseffekt		AC95–265 V, 50/60 Hz	
Öppen kretsspänning		AC115 V	AC230 V
TIG		65 V	
	Märk ingångsström	32,2 A	21,1 A
	Nominell ineffektkapacitet	3,5 kVA	4,7 kVA
	Utgångsströmmråde	DC: 5–160 A AC: 20–160 A	DC: 5–200 A AC: 20–200 A
	Nominell arbetscykel	25 %	
MMA			
	Märk ingångsström	34,1 A	22,7 A
	Nominell ineffektkapacitet	3,9 kVA	5,6 kVA
	Utgångsströmmråde	10–120 A	10–160 A
	Nominell arbetscykel	30 %	
Effektivitet		80 %	
Effektfaktor		0,95	
Tom statsmakt		γ50 W	
skyddsklass		IP23S	
Isoleringsklass		H	
Mått LxBxH		490x165x341 mm	
Nettovikt		11,9 kg	



Standardtillbehör

- 4M SGT26-S1 180A TIG fackla
- 3M öronklämma
- 1 st snabbuttag
- 2 st slangklämmor

