

Premium Super Dry Cutter 9435 - The Reference

with Ø 355/90T HM saw blade:



DRY-CUT TECHNOLOGY

Dry cutting without lubricant

- Cuts ferrous and non-ferrous metal tubes, pipes and profiles made of mild steel, stainless steel, aluminium, plastic and composite materials
- No need of lubricant and manual deburring
- **Exclusive blade stabilising system** reduces vibrations
- High torque motor for continuous operation
- Panted quick-release vice for bevel cuts
- Heavy duty angle cutting at 90-75-60-45°
- Optional stand for a complete and save work place
- CE approved operating system



Specifications

Power input	2.400 W
Voltage	230V/50Hz or 115V/50Hz
No load speed	1.400 rpm
Net weight	25 kg
Blade size	355 mm

Maximum cutting capacities in mm

	90° Cutting	45° Miter Cut
Round	Ø 140 / in Inox 125	Ø 102
Square	125 x 125	80 x 80
Rectangular	105 x 155 90 x 180	75 x 100



600526T3



600546



609910

Premium Super Dry Cutter 9435 Ref.

with 355/90T Saw blade 230V 600560T3

with 355/90T Saw blade 115V 608301T3

HM saw blades Ref.

355/90T for stainless steel-
food & construction 600570NSF

14"/120T for very thin steel and
stainless steel 600512

355/90T for thin steel and stainless
steel 600570

355/72T for medium steel and stain-
less steel 600580

355/60T for thick steel and stainless
steel 600590

355/60T for cast iron 600591

355/66T for mild steel 600595

355/96T for aluminum 600594

Accessories (optional)

Stand for PSDC 9435 600526T3

Thinfix- clamp for open profiles 600546

Eccentric clamping system 609910