

# CERTIFICATE

**TÜV NORD CERT GmbH**  
herewith declares that

**Leapton Solar (Changshu) Co., Ltd.**  
No. 9, Sunshine Avenue, Yushan High Technology Industry Zone,  
Changshu City, Jiangsu Province, 215500  
P.R. China

is authorized to provide the product mentioned below with the mark as illustrated:

**Description of product (details see Annex 2):**

**Crystalline Silicon Terrestrial Photovoltaic (PV) Modules**



Valid from: 2023-07-31  
Valid until: 2028-07-30

Certification program:	P12-VA-01 Rev. 17 09.20
Certification fundamental(s):	IEC 61701:2020
Remark:	Test Method 5
	Test duration: 672 hours
Registered No.:	44 780 23 406749 - 233
Manufacturer:	see Annex 1
Test Report No.:	492012601.001
File No.:	PVP04137/23P-05



**TÜV NORD CERT GmbH**  
Certification Body  
Consumer Products

Essen, 2023-07-31

Please also pay attention to the information stated overleaf.



Anlage 1 zum Zertifikat Nr.: / Annex 1 to Certificate No.: 44 780 23 406749 - 233

Seite / Page 1 von / of 1

Aktenzeichen: / File reference: PVP04137/23P-05

2023-07-31

**Manufacturer:**

Manufacturer:

**Lepton Solar (Changshu) Co., Ltd.**

No. 9, Sunshine Avenue, Yushan High Technology Industry Zone,  
Changshu City

Jiangsu Province, 215500, P.R. China

Factory inspection report no.:

862010379.006

**Remark:**

Factory inspection is mandatory to be performed annually. Please refer to factory inspection report for detailed information.



**TÜV NORD CERT GmbH**  
Certification Body  
Consumer Products



**Description of product(s):**

Module types:

**Double Glass PV Modules with 7" Half Cut Mono-crystalline Silicon Solar Cells:**

144 cells: LP182\*182-M-72-MB-\*\*\*W (\*\*\*) = 520-550, in increment of 5)

132 cells: LP182\*182-M-66-MB-\*\*\*W (\*\*\*) = 475-505, in increment of 5)

120 cells: LP182\*182-M-60-MB-\*\*\*W (\*\*\*) = 435-455, in increment of 5)

108 cells: LP182\*182-M-54-MB-\*\*\*W (\*\*\*) = 390-410, in increment of 5)

Maximum system voltage:

1500V

Fuse rating:

25A

Application class:

Class A

Electrical protection class:

Class II

Module types:

**Double Glass PV Modules with 8" Half Cut Mono-crystalline Silicon Solar Cells:**

132 cells: LP210\*210-M-66-MB-\*\*\*W (\*\*\*) = 630-670, in increment of 5)

120 cells: LP210\*210-M-60-MB-\*\*\*W (\*\*\*) = 575-610, in increment of 5)

108 cells: LP210\*210-M-54-MB-\*\*\*W (\*\*\*) = 515-545, in increment of 5)

96 cells: LP210\*210-M-48-MB-\*\*\*W (\*\*\*) = 460-485, in increment of 5)

84 cells: LP210\*210-M-42-MB-\*\*\*W (\*\*\*) = 400-425, in increment of 5)

110 cells: LP210\*210-M-55-MB-\*\*\*W (\*\*\*) = 520-555, in increment of 5)

100 cells: LP210\*210-M-50-MB-\*\*\*W (\*\*\*) = 475-505, in increment of 5)

90 cells: LP210\*210-M-45-MB-\*\*\*W (\*\*\*) = 425-455, in increment of 5)

80 cells: LP210\*210-M-40-MB-\*\*\*W (\*\*\*) = 380-400, in increment of 5)

Maximum system voltage:

1500V

Fuse rating:


30A or 35A

Application class:

Class A

Electrical protection class:

Class II



**TÜV NORD CERT GmbH**  
Certification Body  
Consumer Products



Module types: **Double Glass PV Modules with half-cut 7" n-type TOPCon Bifacial Mono Solar Cells:**  
156 cells: LP182\*182-M-78-NB-\*\*\*W (\*\* = 580-625, in increment of 5)  
144 cells: LP182\*182-M-72-NB-\*\*\*W (\*\* = 555-605, in increment of 5)  
132 cells: LP182\*182-M-66-NB-\*\*\*W (\*\* = 510-555, in increment of 5)  
120 cells: LP182\*182-M-60-NB-\*\*\*W (\*\* = 460-505, in increment of 5)  
108 cells: LP182\*182-M-54-NB-\*\*\*W (\*\* = 410-450, in increment of 5)

Maximum system voltage: 1500V  
Fuse rating: 25A or 30A  
Application class: Class A  
Electrical protection class: Class II

Module types: **Double Glass PV Modules with half-cut 8" n-type TOPCon Bifacial Mono Solar Cells:**  
132 cells: LP210\*210-M-66-NB-\*\*\*W (\*\* = 675-705, in increment of 5)  
120 cells: LP210\*210-M-60-NB-\*\*\*W (\*\* = 615-640, in increment of 5)  
108 cells: LP210\*210-M-54-NB-\*\*\*W (\*\* = 555-575, in increment of 5)  
96 cells: LP210\*210-M-48-NB-\*\*\*W (\*\* = 490-510, in increment of 5)  
84 cells: LP210\*210-M-42-NB-\*\*\*W (\*\* = 430-445, in increment of 5)

Maximum system voltage: 1500V  
Fuse rating: 30A or 35A  
Application class: Class A  
Electrical protection class: Class II

Remark:

For detailed product information, please refer to CDF (Constructional Data Form) in Annex 1 of test report.



TÜV NORD CERT GmbH  
Certification Body  
Consumer Products