

# GOODWE

## SDT G2 Series

17-25kW | 2 MPPTs | Three Phase

The GoodWe 17-25kW SDT series inverter is especially designed for three-phase residential and small commercial projects. With its compact design, the SDT inverter is 45% smaller than the first generation. The inverter is also light and easy to install. The maximum efficiency of this inverter is as high as 98.4%. With an advanced ventilation system, the inverter is able to dissipate heat efficiently. In addition, it can be customised with an integrated LCD screen.



Compatible with bifacial modules



150% DC input oversizing



110% AC output overloading



Max. Efficiency 98.4%



Compact and light weight

Technical Data	GW17KT-DT	GW20KT-DT	GW25KT-DT
<b>PV String Input Data</b>			
Max. DC Input Power (Wp)	25500	30000	37500
Max. DC Input Voltage (V)	1100	1100	1100
MPPT Operating Voltage Range (V)	200~950	200~950	200~950
Starting Voltage (V)	180	180	180
Nominal DC Input Voltage (V)	620	620	620
Max. Input Current per MPPT (A)	25 / 25	25 / 25	37.5 / 25
Max. Short Circuit Current per MPPT (A)	31.2 / 31.2	31.2 / 31.2	46.8 / 31.2
Number of MPPTs	2	2	2
Number of Strings per MPPT	2 / 2	2 / 2	3 / 2
<b>AC Output Data</b>			
Nominal Output Power (W)	17000	20000	25000
Nominal Output Apparent Power (VA)	17000	20000	25000
Max. Output Apparent Power (VA)	19000*1	22000*1	27500*1
Nominal Output Voltage (V)		400, 3L / N / PE	
Output Voltage Range (V)	180~270	180~270	180~270
Nominal AC Grid Frequency (Hz)	50 / 60	50 / 60	50 / 60
AC Grid Frequency Range (Hz)	45~55 / 55~65	45~55 / 55~65	45~55 / 55~65
Max. Output Current (A)	28.8	31.9	40.8
Nominal Output Current (A)	24.5	28.9	36.1
Output Power Factor	~1 (Adjustable from 0.8 leading to 0.8 lagging)		
Max. Total Harmonic Distortion	<3%	<3%	<3%
<b>Efficiency</b>			
Max. Efficiency	98.4%	98.4%	98.4%
European Efficiency	>97.7%	>97.7%	>97.7%
<b>Protection</b>			
Anti-Islanding Protection	Integrated	Integrated	Integrated
DC Reverse Polarity Protection	Integrated	Integrated	Integrated
DC Insulation Resistor Detection	Integrated	Integrated	Integrated
DC Surge Arrester	Type III (Type II Optional)		
AC Surge Arrester	Type III		
Residual Current Monitoring Unit	Integrated	Integrated	Integrated
AC Over Current Protection	Integrated	Integrated	Integrated
AC Short Protection	Integrated	Integrated	Integrated
AC Over Voltage Protection	Integrated	Integrated	Integrated
DC Arc Fault Circuit Interrupter	Optional	Optional	Optional
<b>General Data</b>			
Operating Temperature Range (°C)	-30~60	-30~60	-30~60
Relative Humidity	0~100%	0~100%	0~100%
Operating Altitude (m)	≤4000	≤4000	≤4000
Cooling Method	Smart Fan Cooling	Smart Fan Cooling	Smart Fan Cooling
Display	LCD, LED / Wi-Fi+APP	LED+LCD / Wi-Fi+APP	LED+LCD / Wi-Fi+APP
Communication	WiFi / LAN / RS485		
Communication Protocol	SunSpec Modbus		
Weight (Kg)	25	25	25
Size (Width × Height × Depth mm)	415 × 511 × 175	415 × 511 × 175	415 × 511 × 175
Ingress Protection Rating	IP65	IP65	IP65
Night Power Consumption (W)	<1	<1	<1
DC Connector	MC4 (2.5~4mm <sup>2</sup> )		
Topology	Transformerless		

\*1: For Belgium Max. Output Apparent Power (VA): GW17KT-DT is 17000; GW20KT-DT is 20000; GW25KT-DT is 25000.

\*: Please visit GoodWe website for the latest certificates.



Color Options: White (EMEA), Red (None-EMEA)