



Blowoff Valve 50mm

Assembly Instructions
© Nuke Performance AB 2010

For more information visit:
www.nukeperformance.com

- | | |
|--------------------------------|-----------------------------|
| 1 Pneufit 1/4 G/ 6mm | 5 O-Ring 70 * 1,8 mm |
| 2 M4*10 Stainless steel | 6 Piston |
| 3 Top | 7 O-Ring 48 * 1,5 mm |
| 4 Spring | 8 Bottom |

Product information

For more info contact your local retailer.

For use on turbo-charged and super-charged applications.

The body and all internal components are CNC-machined from 6082 aluminium alloy.

It features a large 50 mm valve; we believe this is the largest valve available with the highest flow capacity.

The design and finish gives a very clean and unique appearance.

The Blowoff Valve is anodised for a long lasting, corrosion-free appearance.

Technical information

For more info contact your local retailer.

CNC manufactured from aluminium alloy 6082.

The valve seal utilizes a Viton O-ring that is glued in place to prevent the possibility of sticking to the seat and pulling out.

The Blowoff Valve also comes with one air fitting, with over sized 1/4 connection for quick and actuator response.

The Blowoff Valve and housing are available in black or blue color.



This product is designed, developed and manufactured by Nuke Performance AB in Sweden.

Use Lubricant before tightening fittings and always use extra care when handling any kind of fuel.

All our products are installed at your own risk and could damage your equipment, engine or vehicle, unless they are properly installed.

Information:

Design combined with top quality performance.

For more information about the products and retailers visit

www.nukeperformance.com

nuke
PERFORMANCE