



Fuel Filter Slim

Assembly Instructions

© Nuke Performance AB 2012

For more information visit:

www.nukeperformance.com

- | | |
|-------------------------------|-------------------------|
| 1 3/4 UNF-AN-8 Fitting | 5 Filter Element |
| 2 O-ring 19,1 * 1,6 mm | 6 Filter House |
| 3 Filter Ends | 7 Spring |
| 4 O-ring 44,6 * 2,4 mm | |

Product information

For more info contact your local retailer.

For use on turbo-charged, super-charged and Naturally aspirated engine applications.

Our filters is An inexpensive insurance policy to protect your engine.

Designed to stand up to the destructive properties of alcohol fuels, including methanol and ethanol.

• High-flow, 10-micron or 100-micron , cleanable element. Stands high flow with minimal pressure drop.

3/4 Unf Ports, available Fittings to adapt these filters to AN-10, -08 and -06 line.

Slim design for easy mounting with standard clamps and in confined spaces.

Technical information

For more info contact your local retailer.

Aluminium extrusion 6062-T6.

Fuel filter with 3 / 4 UNF thread.

Delivered with two dash 8 and a replaceable filter element, either 10-micron or 100-micron.



This product is designed, developed and manufactured by Nuke Performance AB in Sweden.

Use Lubricant before tightening fittings and always use extra care when handling any kind of fuel.

All our products are installed at your own risk and could damage your equipment, engine or vehicle, unless they are properly installed.

Information:

Design combined with top quality performance.

For more information about the products and retailers visit

www.nukeperformance.com

nuke
PERFORMANCE