# Godox 神牛

# LED Video Light

## LEDM150 Mini LED Video Light 迷你LED摄影灯

**深圳市神牛摄影器材有限公司**
**GODOX Photo Equipment Co., Ltd.**
地址/Add: 深圳市宝安区福永镇福洲大道西新和村华发工业园A4栋
Building A4, Xinhe Huafa Industrial Zone, Fuzhou RD West, Fuyong
Town, Baoan District, Shenzhen 518103, China
电话/Tel: +86-755-29609320(8062)　　传真/Fax: +86-755-25723423
邮箱/E-mail: godox@godox.com
http://www.godox.com

705-LE1500-00　　　　　　　Made In China　　　FC C€ ♻ RoHS ☒

Instruction Manual | 说明手册
Chinese English Bilingual | 中英文双语

型号: LEDM150

# Foreword

Thank you for purchasing this Godox product!
**LEDM150** Mini video light is excellent for macrophotography, wedding shooting, product shooting, photojournalistic and video recording, etc. The lightweight and portable light provides high brightness and convenient operation.

**Features:**
● High-quality LED bulbs
● Built-in lithium battery with great portability
● Soft light and even illumination
● Included with a L-type bracket
● Fits almost any cameras, camcorders and mobile phones

# ⚠ Warning

⚠ Always keep this product dry. Do not use in rain or in damp conditions.
⚠ Do not disassemble. Should repairs become necessary, this product must be sent to an authorized maintenance center.
⚠ Keep out of reach of children.
⚠ As this product do not have waterproof function, please take measures of waterproof in rainy or damp environment.
⚠ Do not use the flash unit in the presence of flammable gases, chemicals and other similar materials. In certain circumstance, these materials may be sensitive to the strong light emitting from this flash unit and fire or electromagnetic interference may result.
⚠ As this product has built-in lithium battery, do not disassemble, impact, squeeze or put it into fire. If serious bulge occurs, please do not use. Do not use or store the product if the ambient temperature reads over 50°C. Please charge the product with specialized charger and correctly operate it within the defined voltage and working temperate according to the instruction manual.

# Parts

• **Body**

Select Dial for Light Brightness
LED Beads
ON/OFF Power Switch
USB Port

Diffuser
Mobile Phone Mounting Bracket
1/4" Bracket Mounting Hole

Battery Indicator
Charging Status Indicator Lamp
Heat Dissipation Groove
Locking Ring
L-type Bracket

# Power Management

**1. Power Supply**
   Built-in large capacity lithium battery 3.7V/3000mAh.


Battery Indicator

● LEDM150 is able to provide the maximum brightness continously up to 60 minutes
   when fully charged.
   **Note:** The indicator light is to display the battery level, when the light is blinking,
      please charge in time.

**2. Charging the Battery**
   ● Insert the mobile phone charger to the USB Port, after 4 hours, the light can be fully
      charged (with 5V1A charger).
      The Status Indicator Lamp lights up when charging and turn off when the battery is
      fully charged.


USB Port

# Using the Video Light

**1. By the Handle**
   ● Install the L-type Bracket onto the 1/4" Bracket
      Mounting Hole.
   ● tighten the upper locking ring of the L-type Bracket.



**2. On the Light Stand**
   ● Install the L-type Bracket onto the 1/4" Bracket
      Mounting Hole and tighten the upper locking ring
      of the L-type Bracket.
   ● Install the light stand onto the 1/4" Bracket
      Mounting Hole.



**3. On the Mobile Phone**
   ● Push into and lock the Mounting Bracket from the
      right direction of the light, pull out from the
      opposite direction of pushing in.
   ● Install the Mobile Phone onto the Mounting
      Bracket.

# Operation

**1. Before Usage**

- Switch the power on, the video light giving out light.



**2. Light Brightness Adjustment**

- Turn the Select Dial for Light Brightness to adjust the light brightness.
- Light Brightness Range: 10%-100%



# What's in the Box of LEDM150?

| NO. | Included Item | LEDM150 |
|-----|---------------|---------|
| 1 | LED Video Light | 1 PC |
| 2 | L-type Bracket | 1 PC |
| 3 | Diffuser | 1 PC |
| 4 | Mobile Phone Mounting Bracket | 1 PC |
| 5 | USB Cord | 1PC |



Diffuser

USB Cord

L-type Bracket

LED Video Light

Mobile Phone
Mounting Bracket

# Technical Data

| LED Light | LEDM150 |
|-----------|---------|
| Built-in Lithium Battery | 3.7V-3000mAh |
| Power | Max. 9W |
| Color Temperature | 5600K±300K |
| Brightness(LUX) | 1029 (0.5 m) |
| Color Rendering Index | >95 |
| TLCI | ≥94 |
| Light Brightness Range | 10%~100% |
| LED Beads Quantity | 150 |
| Operation Temperature | -10~50°C |
| Dimension | 132mm*80mm*20mm(not with the L-type Bracket and Mounting Bracket) |
| Net Weight | 170g |

\* Product design and specifications are subject to change without notice.