



HIGH-PRESSURE WASHERS - HOT WATER STATIONARY

IWD-H

PRESSURE

100÷200
bar

FLOW RATE

720÷1260
l/h

ABSORBED POWER

3,2÷9,5
kW

EXCLUSIVE CHARACTERISTICS

- ▶ DELAYED TOTAL STOP - DTS
- ▶ MICRO LEAKAGE CONTROL - MLC
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ NOZZLE CLOGGING CONTROL - NCC
- ▶ INFRARED FLAME CONTROL SYSTEM - FCS
- ▶ BOILER IGNITION DELAY - IBD
- ▶ FUEL LEVEL CONTROL - FLC (OPTIONAL)
- ▶ ANTI-SCALE LEVEL CONTROL - ALC (OPTIONAL)
- ▶ LIMESCALE/CORROSION PROTECT UNIT - LCPU
- ▶ INTELLIGENT AUTOMATIC SWITCH OFF - IASF



MOST FREQUENTLY USE



INNOVATIONS



SPECS



STAINLESS STEEL
STRUCTURE



PILOT LIGHTS INDICATING
MACHINE AND BURNER
FUNCTIONING, PLUS FLAME
CONTROL



PROFESSIONAL PRESSURE
GAUGE ENSURING A
CONSTANT CONTROL OF
WORKING PRESSURE

TECHNICAL DATA

		MUR. IWD-H D1012PI M	MUR. IWD-H D1615PI T	MUR. IWD-H D1618PI T	MUR. IWD-H D2015PI T	MUR. IWD-H D1521PI T	MUR. IWD-H D2021PI T
Code		IDAC48036	IDAC48037	IDAC48038	IDAC48039	IDAC48040	IDAC48041
PERFORMANCE							
Operating pressure	bar/Mpa	100/10	160/16	165/16,5	200/20	150/15	200/20
Flow rate	l/h	720	900	1080	900	1260	1260
Outlet water max. temperature	°C	30-120	30-120	30-120	30-120	30-120	30-145
Power supply	Ph-V-Hz/A	1-230-50/14	3-400-50/10,5	3-400-50/13	3-400-50/14	3-400-50/13	3-400-50/16
Absorbed power	kW	3,2	6,5	7,2	7,2	7,2	9,5
Motor pole/rpm		4-1400	4-1400	4-1400	4-1400	4-1400	4-1400
Boiler thermal power	kW	67	67	88	88	88	88
Fuel consumption	l/h	5,8	5,8	7,4	7,4	7,4	7,4
Remote control		DTS	DTS	DTS	DTS	DTS	DTS
Fuel tank	l	optional (25 l)	optional (25 l)	optional (25 l)	optional (25 l)	optional (25 l)	optional (25 l)
Detergent tank	l	optional (2x25 l)	optional (2x25 l)	optional (2x25 l)	optional (2x25 l)	optional (2x25 l)	optional (2x25 l)
Detergent delivery		high pressure	high pressure	high pressure	high pressure	high pressure	high pressure
Anti-scale tank	l	2	2	2	2	2	2
Pump/head/pistons		ipg plunger/brass/ ceramic	ipg plunger/brass/ ceramic	ipg plunger/brass/ ceramic	ipg plunger/brass/ ceramic	ipg plunger/brass/ ceramic	ipg plunger/brass/ ceramic
Dimension (LxWxH)	cm	122x60x75	122x60x75	122x60x75	122x60x75	122x60x75	122x60x75
Weight	kg	170	185	190	186	186	210

STANDARD EQUIPMENT

CODE: IPPR40025
HANDGRIP G6000



CODE: LCPR40087
EXTENSION P70 INOX
(FOR 1012/1615/2015)



CODE: LCPR40159
EXTENSION P70 INOX 0°
(FOR 1618/1521/2021)



CODE: UGLN49993
H.P. NOZZLE 1/4 25055
(FOR 1012/1615)



CODE: UGLN49995
H.P. NOZZLE 1/4 25065
(FOR 1618/2021)



CODE: UGLN49987
H.P. NOZZLE 1/4 15045
(FOR 2015)



CODE: UGLN49997
H.P. NOZZLE 1/4 15075
(FOR 1521)



CODE: TBAP40008
H.P.HOSER1 10 m 5/16"
(FOR 1012/1615/1618/1521)



CODE: TBAP40009
H.P.HOSER2 10 m 5/16"
(FOR 2015)



CODE: TBAP40010
H.P.HOSER2 10 m 3/8"
(FOR 2021)



OPTIONAL ACCESSORIES

CODE: AVTB39119
INOX HOSE REEL KIT



CODE: KTRI28914
ROTATING ARM



CODE: LCLC41140
LANCE FOR WASHING
FLOOR - INOX



CODE: LCPR29360
MUDGUARD LANCE



CODE: KTRI48114
REMOTE CONTROL WITH
DETERGENT + WAX CONTROL



CODE: KTRI48110
WALL FIXING BRACKET



CODE: KTRI48111
STAND



CODE: LCPR41973
TURBO LANCE Ø0,55 -
(FOR 1012/1615)



CODE: LCPR88522
TURBO LANCE Ø0,65 -
(FOR 1618/2021)



CODE: LCPR40088
TURBO LANCE Ø0,80 -
(FOR 2015/1521)



CODE: LAFN48112
FLUE EXTENSION



CODE: LCPR13557
SANDBLASTER KIT Ø 1,6 mm
(FOR 1012/1615)



CODE: LCPR14860
SANDBLASTER KIT Ø 1,7 mm
(FOR 1618/2021)



CODE: LCPR14859
SANDBLASTER KIT Ø 1,5 mm
(FOR 2015)



CODE: PRCH40041
SAND BAG 25 Kg



CODE: MPVR13701
25 l FUEL TANK 1 PCS



CODE: MPVR13701
25 l DETERGENT TANK
2 PCS

