



HIGH-PRESSURE WASHERS - HOT WATER

PW-H50 PLUS

PRESSURE

130-200
bar

FLOW RATE

600-1000
l/h

ABSORBED POWER

3,0-6,4
kW

EXCLUSIVE CHARACTERISTICS

- ▶ DELAYED TOTAL STOP - DTS
- ▶ INTELLIGENT AUTOMATIC SWITCH OFF - IASF
- ▶ MICRO LEAKAGE CONTROL - MLC
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ NOZZLE CLOGGED CONTROL - NCC
- ▶ BOILER IGNITION DELAY - IBD
- ▶ WORKING HOURS COUNTER - WHC
- ▶ ELECTRONIC TEMPERATURE STABILIZER CONTROL - ETSC
- ▶ LIMESCALE/CORROSION PROTECTION UNIT - LCPU
- ▶ ANTI-SCALE LEVEL CONTROL - ALC
- ▶ FUEL LEVEL CONTROL - FLC
- ▶ MAINTENANCE CHECK LED - MCL



PW-H50 PLUS



PW-H50/4 PLUS

MOST FREQUENTLY USE

AUTOMOTIVE



AGRICULTURE



CONSTRUCTION INDUSTRY



MUNICIPALITIES



DIY AND GARDENING



HEAVY INDUSTRY



INNOVATIONS



G6000™
CERAMIC
TECH GUN



MSCT™
MULTIFUNCTION
SAFETY
CONTROL



ETC™
ELECTRONIC
TEMPERATURE
CONTROL



M421
ANTI-SCALE

SPECS



CONTROL PANEL WITH INDICATORS LAMPS



ERGONOMIC HANDLE PROVIDED WITH LANCE HOLDER FOR AN EASY TRANSPORT



ACCESSORIES STORAGE COMPARTMENT

TECHNICAL DATA

		DELAYED TOTAL STOP				
3 WHEELS		PW-H50P D1310P4 M	PW-H50P D1012P4 M	PW-H50P D1813P4 T	PW-H50P D1915P4 T	PW-H50P D2017P4 T
Code		IDAC40873	IDAC40874	IDAC40875	IDAC40876	IDAC40877
4 WHEELS		PW-H50P/4 D1310P4M	PW-H50P/4 D1012P4M	PW-H50P/4 D1813P4T	PW-H50P/4 D1915P4T	PW-H50P/4 D2017P4T
Code		IDAC40883	IDAC40884	IDAC40885	IDAC40886	IDAC40887
PERFORMANCE						
Operating pressure	bar/Mpa	30-130/3-13	30-100/3-10	30-180/3-18	30-190/3-19	30-200/3-20
Flow rate	l/h	300-600	360-720	450-800	450-900	500-1000
Outlet water temperature	°C	30-140	30-140	30-140	30-140	3-140
Power supply	Ph-V-Hz/A	1-230-50/13,8	1-230-50/14	3-400-50/9,7	3-400-50/10,6	3-400-50/13,2
Absorbed power	kW	3,1	3,2	5	5	6,4
Motor pole/rpm		4-1400	4-1400	4-1400	4-1400	4-1400
Remote control		DTS	DTS	DTS	DTS	DTS
Pump/head/pistons		lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic
Boiler thermal power	kW	40	55	70	70	≥70
Fuel consumption	kg/h	3,2	5,8	5,8	5,8	5,8
Dimension (LxWxH)	cm	110x70x90	110x70x90	110x70x90	110x70x90	110x70x90
Weight	kg	107	109	120	122	140

STANDARD EQUIPMENT

CODE: IPPR40020
HANDGRIP G6000



CODE: LCPR40087
P70 INOX EXTENSION



CODE: UGLN49986
HIGH-PRESSURE NOZZLE
(FOR 1310/1813)



CODE: UGLN05200
HIGH-PRESSURE NOZZLE
(FOR 1012)



CODE: UGLN49987
HIGH-PRESSURE NOZZLE
(FOR 1915/2017)



CODE: TBAP25324
HIGH-PRESSURE HOSE
MT 10



OPTIONAL ACCESSORIES

CODE: SPID24911
ROTATING HYDROBRUSH
LANC E P70



CODE: SPID24939
FIXED HYDROBRUSH
LANC E P70



CODE: LCLC41140
INOX FLOOR WASH LANCE



CODE: KTRI40235
HOSE REEL KIT



CODE: RCIN10810
HOSE COUPLING M22



CODE: KTRI29377
FEEDING KIT



CODE: TBAP23853
DRAIN KIT MT 10



CODE: KTRI29366
PLUNGER EJECTOR DEVICE



CODE: LCPR40014
M22 D.1,30
(FOR 1310/1813)
TURBO LANCE



CODE: LCPR40135
P70 M22 0,45
(FOR 1915)
TURBO LANCE



CODE: LCPR14859
SANDBLASTER KIT D.1,5
(FOR 1915/2017)



CODE: LCPR14858
SANDBLASTER KIT D.1,4
(FOR 1310/1813)



CODE: LCPR13557
SANDBLASTER KIT D.1,6
(FOR 1012)



CODE: PRCH00065
SAND BAG 50KG



CODE: PRCH40039
ANTI-SCALE TREATMENT
M421 1KG X6



CODE: PRCH40040
ANTI-SCALE TREATMENT
M421 10KG



CODE: KTRI40316
MAINTENANCE KIT 500H
(FOR 1310)



CODE: KTRI40314
MAINTENANCE KIT 500H
(FOR 1813/1915)



CODE: KTRI40430
MAINTENANCE KIT 500H
(FOR 1012)



CODE: KTRI40431
MAINTENANCE KIT 500H
(FOR 2017)



IP Cleaning S.p.A.

Viale Treviso 63 - 30026 Summaga di Portogruaro (VE) - Italy
Tel. +39 0421 205511 - Fax +39 0421 204227 - info@ipcworldwide.com - www.ipcworldwide.com