

## REFLEX G MOPCLOTH 50% UMF 50% PE, 40% recycled material

#### Make a difference with REFLEX:



Outstanding Performance & Versatility:

Deep Cleaning. Multifunctional and Ergonomical Up to 50 sqm more per mopcloth



Climate & Eco friendly:

Less water and chemicals. Residue Free Cleaning



Improves cleaning economy:

Saves time and space and cut total costs

Saves time and space and cut total costs			
Product code	Colour code	Dimension	
23-4059	Grey	54 x 22,5 cm	REFLEX G MOPCLOTH 50% UMF, 50% PET
	Colour tagged		40% recycled material, multiple use, 65 grs/pcs
Package:	5 pcs in environmental friendly cardboard pack, 32 pcs 5-pack per transport box		

Application areas:

The REFLEX 2-in-1 cleaning system is designed for all types of smooth and sealed hard top floorings. Main application areas, in case of less conditioned floors:



Public Areas & General Buildings



Food Industry & HoReCa

How to use the system:

REFLEX G MOPCLOTH is double sided and is used in conjunction with REFLEX POWER SQUEE-GEE 50 cm and REFLEX EXTENDABLE HANDLE 100/180 cm.

#### **CHARGING:**



REFLEX G MOPCLOTH can be pre-prepared/charged with clean tap water or processed water. Optional: Chemicals suitable for UMF can be diluted according to manufacturer's instructions.

## CHARGING G MOPCLOTHS ON THE TROLLEY:

- 1. Put G MOPCLOTHS in a container, e.g. 6 Ltr. Rectangle bucket or box with lid.
- 2. Poor the desired fluid equally over the cloths inside the container.
- 3. Leave for a while with closed lid. Ready to clean!

## **ABOUT DOSING:**

Avoid overdosing regardless the charging liquid.

Some chemicals may cause damage to user material and or environment.

Depending on floor circumstances, charge the G MOPCLOTH with 60-120 ml per MOPCLOTH.

# Eco Labelled:





#### Rekola support Residue Free Cleaning.

Rekola is part of a group of manufactures determined to eliminate residue of dirt and chemicals that can harm people's health REFLEX G MOPCLOTHS are designed to reduce and remove residue that resist traditional cleaning methods.



Maintenance				
Laundry:	Rinse twice cold to ensure all cleaning chemicals are removed.			
(e=1 0)	Main program for synthetic fibres at 60°C or less is preferred.			
	Rinse twice after at 40° ensuring all laundry agents are removed.			
	Adjust temperatures and water volumes accordingly.			
	Machine drums can be filled with MOPCLOTHS up to 80% load (According Weber & Leucht			
	laundry test DIN EN ISO 6330)			
	In case of drying use tumble drying at 40°C.			
	t use bleach or softener.			
	Low water level during processing or overloading washing machine (max 80% of door win-			
	dow) may cause irreversible damage to cloths.			
Disinfection:	Non-bleach disinfectant* laundry agent and autoclaving may be used if required *e.g. perox-			
	ide based; this may affect colours.			
Durability:	500 washing cycles at 60°C or 200 washing cycles at 85°C. Rough surfaces like safety flooring			
	may influence reduce lifetime expectations.			
Components				
Body:	50% split Ultra Microfibre / 50% PET , 90% PET 10 PA , 40% recycled material			
	and UMF F= <b>0,154 Dtex.</b>			
Borders:	Overlock 100% PET. Sliding strip TPU and PET Mesh			
4 Colour tag:	PET colour fast			
Characteristics				
Shrinkage:	SGS tested < 6% at recommended washing instructions. This can cause slight deformation,			
	this does not affect the functionality.			
Colour fastness	4-5. standard request $\geq$ 3-4			
Charging	3,9 DAC value. standard request minimum 2,5			
Abrasion	6,2 Gloss differential. standard request < 20			
Weber & Leucht	Ceramic Tile SF 11 Dust A23 Damp 93% standard request ≥ 70			
S301/1.3	PVC- Flooring PL-03 Dust A23 Damp 93% standard request ≥ 70			
dirt removal	Ceramic Tile SF 11 Muddy dirt A05 Damp 90% standard request ≥ 70			
	PVC- Flooring PL-03 Muddy dirt A05 Damp 90% standard request $\geq 70$			
Non-Touch	In conjunction with REFLEX POWER SQUEEGEE, dirty cloths are not touched when de-			
	mounting.			
Patent:	FI2010000028 Floor Maintenance Device and Cloth.			
<b>Disposing:</b> REFLEX G MOPCLOTHS are purely synthetic: may be used for recycling programs of their high arguments and with an argument and with an argument and with an argument and with a second wit				
	of their high energy value and with no emissions other than $CO_2$ and water can be safely disposed by controlled energy-supply programs.			
	posed by controlled effergy-supply programs.			

# Guarantee

500 times use and laundries according producers guidelines at 60°C, under general hygiene cleaning circumstances , at a maintained non-safety sealed floor.

Extended usage can be achieved if optimal laundry and cleaning conditions are considered.

For instruction and details ask your distributor.