

REFLEX S MOPCLOTH 50% UMF 50% PET, 35% recycled material



Outstanding Performance & Versatility:

Deep Cleaning. Multifunctional and Ergonomical Up to 50 sqm more per mopcloth



Climate & Eco friendly:

Less water and chemicals. Residue Free Cleaning



Improves cleaning economy:

Saves time and space and cut total costs

Product code	Colour code	Dimension	
23-7059	grey	54 x 22,5 cm	REFLEX S MOPCLOTH 50% UMF, 35% recycled material multiple use, 85 grs/pcs
Package:	5 pcs in environmental friendly cardboard pack, 20 pcs 5-pack per transport box		

Application areas:

The REFLEX 2-in-1 cleaning system is designed for all types of smooth and sealed hard top floorings. Main application areas:



Healthcare sector



Public Areas & General Buildings



Food Industry & HoReCa

How to use the system:

REFLEX S MOPCLOTH is double sided and is used in conjunction with REFLEX POWER SQUEE-GEE 50 cm and REFLEX EXTENDABLE HANDLE 100/180 cm.



CHARGING:

REFLEX S MOPCLOTH can be pre-prepared/charged with clean tap water or processed water. Optional: Chemicals suitable for UMF can be diluted according to manufacturer's instructions.

CHARGING S MOPCLOTHS ON THE TROLLEY:

- 1. Put S MOPCLOTHS in a container, e.g. 6 Ltr. Rectangle bucket or box with lid.
- 2. Poor the desired fluid equally over the cloths inside the container.
- 3. Leave for a while with closed lid. Ready to clean!

ABOUT DOSING:

Avoid overdosing regardless the charging liquid.

Some chemicals may cause damage to user material and or environment.

Depending on floor circumstances, charge the S MOPCLOTH with 60-120 ml per MOPCLOTH.

Eco Labelled:





Rekola support Residue Free Cleaning.

Rekola is part of a group of manufactures determined to eliminate residue of dirt and chemicals that can harm people's health REFLEX H MOPCLOTHS are designed to reduce and remove residue that resist traditional cleaning methods.

For more information please contact Rekola



Maintenance				
Laundry:	Rinse twice cold to ensure all cleaning chemicals are removed.			
(O= O	Main program for synthetic fibres at 60°C or less is preferred.			
	Rinse twice after at 40 ⁰ ensuring all laundry agents are removed.			
	Adjust temperatures and water volumes accordingly.			
	Machine drums can be filled with MOPCLOTHS up to 80% load (According Weber & Leucht			
	laundry test DIN EN ISO 6330)			
	In case of drying use tumble drying at 40°C.			
	Do not use bleach or softener.			
	Low water level during processing or overloading washing machine (max 80% of door win-			
	dow) may cause irreversible damage to cloths.			
Disinfection:	Non-bleach disinfectant* laundry agent and autoclaving may be used if required *e.g. perox-			
	ide based; this may affect colours.			
Durability:	500 washing cycles at 60°C or 200 washing cycles at 85°C. Rough surfaces like safety flooring			
	may influence reduce lifetime expectations.			
Components				
Body:	50% split Ultra Microfibre 80% PET 20 PA F= 0,154 Dtex, mixed with 50% PET film,			
,	,			
Borders	Overlock 100% PET. Sliding strip TPU and PET Mesh			
4. Colour tag	PET colourfast			
Characteristics				
Shrinkage:	SGS tested <6% at recommended washing instructions. This can cause slight deformation, this			
	does not affect the functionality.			
Colour fastness	4. $standard request \ge 3-4$			
Charging	4,2 DAC value. standard request minimum 2,5			
Abrasion	The abrasion generated during use, is not advised for usage on softer material surfaces			
Weber &	Ceramic Tile SF 11 Dust A23 Damp 95% standard request ≥ 70			
Leucht	PVC- Flooring PL-03 Dust A23 Damp 95% standard request ≥ 70			
S301/1.3	Ceramic Tile SF 11 Muddy dirt A05 Damp 100% standard request ≥ 70			
dirt removal	PVC- Flooring PL-03 Muddy dirt A05 Damp 100% standard request ≥ 70			
Bacteria	E-coli 99,9 % log >3,34 S. Aureus 99,9 log 2,82			
reduction				
Non-Touch	In conjunction with REFLEX POWER SQUEEGEE, dirty cloths are not touched when de-			
	mounting.			
Patent:	FI2010000028 Floor Maintenance Device and Cloth.			
Disposing:	REFLEX S MOPCLOTHS are purely synthetic: may be used for recycling programs; or because			
	of their high energy value and with no emissions other than ${ m CO_2}$ and water can be safely dis-			
	posed by controlled energy-supply programs.			
Guarantee				

Guarantee

500 times use and laundries according producers guidelines at 60°C, under general hygiene cleaning circumstances , at a maintained non-safety sealed floor.

Extended usage can be achieved if optimal laundry and cleaning conditions are considered.

For instruction and details ask your distributor.