

Ecoline MultiTop Lacquer Polish

Technical Data Sheet
June 2022
Page 1/1



Ecoline



- » *renovation and renewal*
- » *maintains hard-wearing lacquer surfaces*
- » *for surfaces coated with [Ecoline MultiTop](#)*

Product characteristics:

Self levelling care emulsion for quick renovation of floors coated with [Ecoline MultiTop](#). *Ecoline MultiTop Lacquer Polish* glistens slightly. A thin film is formed, the surface is refreshed and small gaps are being impregnated. Dirt cannot adhere easily and cleaning will be considerably facilitated.

Colours:

8152Eco Matt
8153Eco Satin matt

Fields of application:

Especially for *Ecoline* lacquered flooring made of wood and bamboo. Also well suited for furniture and other interior wood (lacquered surfaces).

Preparation:

Sweep and vacuum-clean the floor. If there is any remaining dirt, it has to be cleaned with [Ecoline Wash Care](#). In the case of heavy soiling or worn maintain floor layers, carry out a basic cleaning with [Ecoline Magic Cleaner](#). Continue working not before complete drying! Sand with a [green pad](#) if necessary. Remove sanding dust thoroughly with a dry cloth and vacuum cleaner.

Application:

Shake well before use - do not dilute.
Spread even and sufficiently on the cleaned and dry floor with a fine-fiber wiper ([SAICOS Telescope-Maintenance Cloth](#) - do not process by machine).

Too little application prevents the smooth leveling. Avoid puddles, splashes and drops. Spread evenly – do not polish. Treat larger surfaces in sections. It must not have been dried between sections. Last application should be done in direction of wood grain.

Note:

For heavily worn floors, the use may be repeated after a few months. Parquet and finished floors may never be damp or wet over a long period of time because they react sensitive (swelling). Strongly alkaline cleaning agents will damage the surface. Therefore always use the recommended cleaning and care products.

Drying time:

Under right conditions the surface can be walked on after approx. 30 minutes.

Frequency of care:

once a year or as needed

Best processing temperature:

between 8 °C and 25 °C.

Coverage per liter:

approx. 100 m²
1 cap for approx. 1 m²

Storage:

In sealed container at least 1 year. The liquid product is susceptible to frost. Transport and store frost-free (> 5 ° C).

Safety Instructions – First Aid: Keep out of the reach of children.
Do not fill into food, beverage or other containers used for food-stuffs.

EU limit for clear coatings and stains (cat. A/e): 130 g/l (2010).
Ecoline MultiTop Lacquer Polish contains max. 130 g/l VOC.

Our application advice is provided to the best of our knowledge and based on experiments, however, applies only as a non-binding recommendation and does not exempt you from testing the products supplied by us as to their suitability for the intended purpose. Since the application and processing of the products is beyond our control, the responsibility rests solely with the user. With publishing a new technical data sheet the previous loses its validity.

SAICOS COLOUR GmbH

Carl-Zeiss-Str. 3
D-48336 Sassenberg
☎ +49 2583 3037-0
☎ +49 2583 3037-10
info@saicos.de
www.saicos.de