

Ecoline Magic Cleaner

Technical Data Sheet

June 2022

Page 1/1



Ecoline



- » *intensive cleaner – prior renovation*
- » *for stained, worn down wood and cork surfaces*
- » *cleans table and furniture surfaces and other surfaces such as PVC, linoleum, ceramic, tiles, natural stone*
- » *solvent-free*

Product characteristics:

Ecoline Magic Cleaner – the perfect solution for worn down surfaces: For intensive cleaning of all waxed, oiled or lacquered surfaces. Removes nicotine, grease and dirt films e.g. in bathroom and kitchen. Does not contain bleach. Usable with cleaning machines.

Article number:

8125Eco *Ecoline Magic Cleaner Concentrate*

8126Eco *Ecoline Magic Cleaner Spray (ready-to-use)*

Fields of application:

Intensive cleaning of all waxed, oiled or lacquered surfaces. Also for all other surfaces such as PVC, linoleum, ceramic, tiles, natural stone ... Easy removal of nicotine, grease and dirt films in bathroom and kitchen.

Restrictions on use:

Do not use on untreated wood or cork surfaces as it will hamper a subsequent coating. Discolourations, caused by improper application, may occur on alkaline sensitive surfaces (f.i. oak, chestnut) due to their high tannin content (test in a hidden area).

Preparation:

Dilute *Ecoline Magic Cleaner Concentrate* 1:10 with water (for example 0,5 liter concentrate with 5 liters water).

Processing:

Spread evenly on the floor with soaked joint-wiper, wiper, cloth (or appropriate cleaning machine). Do not pour directly on the surface – do not leave pools on surface.

Leave to act for 5 – 20 min. Treat spots dried during that time again. Remove dissolved dirt with damp joint-wiper, wiper or cloth. Wipe 2 – 3 times with clear water. Wipe dry afterwards. This procedure can be repeated if necessary. *Ecoline Magic Cleaner Spray* can be sprayed directly on the surface.

Coverage per liter: 1 liter *Ecoline Magic Cleaner Concentrate* is sufficient for approx. 11 liters of dilution.

Number of treatments: 1x, if heavily soiled 2x.

Drying time: Depending on weather conditions, dries like a normal damp surface. (Apply an optional new coating only after complete drying.)

Easy maintenance: Maintain surface with [Ecoline Wax Care](#) after complete drying (see care instructions). Sand damaged waxed / oiled wooden or cork surfaces after complete drying with green or black pad / cross grinding pad and renovate partially or completely with [Ecoline Hardwax-Oil](#). Please note the corresponding technical data sheet.

Cleaning of tools: Wash out with plenty of water and let dry.

Storage: In closed container unlimited. The liquid product is not susceptible to frost.

Physical properties:

Density: 0.995 - 1.025 g/cm³

Odour: faint/weak, odorless when dry

Flashpoint: non-flammable

Safety instructions - first aid: Keep out of the reach of children. Do not fill into food, beverage or other containers used for foodstuffs. **Additionally for the undiluted concentrate 8125Eco:** Causes serious eye irritation. Wash hands thoroughly after handling. Wear protective gloves and eye / face protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritations persists: Get medical advice/attention.

GGVSEB / ADR -/-

Our application advice is provided to the best of our knowledge and based on experiments, however, applies only as a non-binding recommendation and does not exempt you from testing the products supplied by us as to their suitability for the intended purpose. Since the application and processing of the products is beyond our control, the responsibility rests solely with the user. With publishing a new technical data sheet the previous loses its validity.

SAICOS COLOUR GmbH

Carl-Zeiss-Str. 3

D-48336 Sassenberg

+49 2583 3037-0

+49 2583 3037-10

info@saicos.de

www.saicos.de